



**CATALOGUE**  
LUBRICANTS, GREASES  
& SPECIAL PRODUCTS





## ORDERS

To order please call:

+30 210 8093 903, +30 210 8093 684

FAX: +30 210 8093 999



# INDEX

---

<b>MAGMA</b>	PASSENGER CAR & LIGHT DUTY VEHICLE ENGINE LUBRICANTS (PCMO)	12
<b>GRANIT</b>	COMMERCIAL & HEAVY DUTY DIESEL ENGINE LUBRICANTS	20
<b>FARMA</b>	LUBRICANTS FOR FARMING MACHINERY	28
<b>LAVA</b>	MOTORCYCLE & OUTBOARD ENGINE LUBRICANTS	30
<b>GEAR</b>	DRIVELINE LUBRICANTS	36
<b>SPECIAL PRODUCTS</b>	AUTOMOTIVE SPECIAL PRODUCTS	44
<b>INDUSTRIAL</b>	INDUSTRIAL LUBRICANTS	50
<b>GREASE</b>	GREASES	62
<b>MARINE</b>	MARINE LUBRICANTS	68



## Tribolite<sup>®</sup> FORMULA

Tribolite<sup>®</sup> Formula is based on an innovative additives "system" which, due to the different polarity of its components, activates strong chemical interactions, hence enhancing to the fullest the protection that the lubricant provides to the engine.

The strong and synergistic action of the components of Tribolite<sup>®</sup> Formula enhances the most important tribological characteristics of the lubricant:

- The consistency of the lubricating film in boundary lubrication conditions
- Wear control in piston areas and springs
- The clean-ability of the oil in the turbocharger area, and
- Fuel savings

Tribolite<sup>®</sup> Formula stands for technological superiority and innovation in lubrication. Cyclon lubricants blended with Tribolite<sup>®</sup> provide extremely high levels of wear protection, engine durability and fuel economy.







## PRODUCT APPROVALS TABLE FOR PASSENGER VEHICLES

PRODUCTS/APPROVALS	ACEA					API				ILSAC
	ACEA A3/B3	ACEA A3/B4	ACEA C2	ACEA C3	ACEA C5	API SP	API SN Plus	API SN	API SL	GF-6A
<b>MOTOR OILS</b>										
CYCLON MAGMA SYN V1 5W30				●				●		
CYCLON MAGMA SYN V1 0W30				●						
CYCLON MAGMA SYN M-FE 0W20					●					
CYCLON MAGMA SYN V-FE 0W20					●					
CYCLON MAGMA SYN DXS 5W30			●	●				●		
CYCLON MAGMA SYN TDI 5W40								●		
CYCLON MAGMA SYN FD 5W20					●			●		
CYCLON MAGMA SYN ULTRA 5W40	●	●						●		
CYCLON MAGMA SYN ULTRA S 5W30						●	●			
CYCLON MAGMA SYN ULTRA S 0W20						●	●			
CYCLON MAGMA HYPER X-200 10W40						●	●			
CYCLON MAGMA HYPER X-200 5W30						●	●			●
CYCLON MAGMA HYPER X-200 5W40						●	●			
CYCLON MAGMA SYN F1 10W40	●	●								
CYCLON MAGMA X-100 10W40	●	●						●		
<b>TRANSMISSION OILS</b>										
CYCLON GEAR EP/GL5 80W90										



**PRODUCTS/APPROVALS**

**MOTOR OILS**

**MB**

**VW**

**ZF**



	MB 229.1H	MB 229.3	MB 229.5	MB 229.51	MB 229.52	MB 229.71	VW 508.00/509.00	VW 504.00/507.00	VW 505.00/505.01	VW 502.00/505.00	ZF TE-ML-05A	ZF TE-ML-12E	ZF TE-ML-16B	ZF TE-ML-17B	ZF TE-ML-19B	ZF TE-ML-21A
CYCLON MAGMA SYN V1 5W30							●									
CYCLON MAGMA SYN V1 0W30							●									
CYCLON MAGMA SYN M-FE 0W20					●											
CYCLON MAGMA SYN V-FE 0W20							●									
CYCLON MAGMA SYN DXS 5W30			●	●				●								
CYCLON MAGMA SYN TDI 5W40			●													
CYCLON MAGMA SYN FD 5W20																
CYCLON MAGMA SYN ULTRA 5W40		●							●							
CYCLON MAGMA SYN ULTRA S 5W30																
CYCLON MAGMA SYN ULTRA S 0W20																
CYCLON MAGMA HYPER X-200 10W40																
CYCLON MAGMA HYPER X-200 5W30																
CYCLON MAGMA HYPER X-200 5W40																
CYCLON MAGMA SYN F1 10W40		●														
CYCLON MAGMA X-100 10W40	●															

**TRANSMISSION OILS**

CYCLON GEAR EP/GL5 80W90											●	●	●	●	●	●
--------------------------	--	--	--	--	--	--	--	--	--	--	---	---	---	---	---	---



## PRODUCT APPROVALS TABLE FOR HEAVY DUTY DIESEL VEHICLES

PRODUCTS/APPROVALS	ACEA								API					ROLLS-ROYCE MTU			
	ACEA A3/B4	ACEA E2	ACEA E3	ACEA E5	ACEA E4	ACEA E6	ACEA E7	ACEA E9	API CK-4	API CJ-4	API CI-4+	API CI-4	API SN	API SL	MTU Cat 2	MTU Cat 3	MTU Cat 3.1
<b>PRODUCTS</b>																	
CYCLON GRANIT SYN EURO ULTRA 5W30					●	●	●		●				●				
CYCLON GRANIT SYN EURO MAXX 10W40					●	●	●					●					●
CYCLON GRANIT SYN EURO FLEET 10W40				●		●						●			●		
CYCLON GRANIT VDS 10W40							●		●		●						
CYCLON GRANIT VDS 15W40							●		●				●				
CYCLON GRANIT SYN SHPD PLUS 10W40	●			●		●						●		●			
CYCLON GRANIT SYN SHPD 15W40	●			●		●						●		●			
CYCLON GRANIT MAXIMUM 15W40		●	●	●		●						●		●	●		
CYCLON GRANIT SUPER 20W50		●	●	●		●						●		●			
CYCLON GRANIT EXTRA 15W40		●															
CYCLON GRANIT PRIME 40		●															
<b>INDUSTRIAL OILS</b>																	
CYCLON HYDRAULIC ISO 46																	
CYCLON TITANUS EP 68, 150																	







**PRODUCT APPROVALS TABLE FOR MARINE LUBRICANTS**

**PRODUCTS/APPROVALS**

**LUBRICANTS**



LUBRICANTS	MAN ENERGY SOLUTIONS	WinGD	MAN DIESEL & TURBO	WARTSILA
CYCLON NAUTILUS HEAVY XT 140 SAE 50	●			
CYCLON NAUTILUS HEAVY XT 100 SAE 50	●	●		
CYCLON NAUTILUS HEAVY SAE 50	●	●		
CYCLON NAUTILUS LS 50 SAE 50	●	●		
CYCLON ARMOR MEDIUM SAE 30	●	●		
CYCLON POSEIDON HT 3020			●	
CYCLON POSEIDON HT 4020			●	
CYCLON POSEIDON HT 3030			●	●
CYCLON POSEIDON HT 4030			●	●
CYCLON POSEIDON HT 3040			●	●
CYCLON POSEIDON HT 4040			●	●
CYCLON POSEIDON HT 3050			●	●
CYCLON POSEIDON HT 4050			●	●





**MAGMA**



## **PASSENGER CAR & LIGHT DUTY VEHICLE ENGINE LUBRICANTS** (PCMO)

MAGMA engine oils are the result of our latest research and development efforts, stemming from our 35 years of hands-on experience in formulating, testing and blending superior technology lubricant products for the real world; high added-value passenger and light duty commercial lubricants that exceed the performance challenges of the world's leading car manufacturers, as these are shaped by their customers' (i.e. the drivers') current needs: fuel economy, wear minimization & turbocharger protection.

**In particular, MAGMA lubricants will provide up to 3.5% additional fuel economy benefits\*, while they will enhance the offered engine protection from wear to a percentage up to 68%.**

**MAGMA engine oils - manufactured in the EU for  
the real world - stand for complete engine  
protection and optimal performance.**

\*As demonstrated in M111 Fuel Economy test for MAGMA SYN FD 5W-20.









## MAGMA SYN V-FE

Top-tier, fully synthetic, low viscosity, high fuel economy, midSAPS motor oil for all latest-generation VW engines running on gasoline/gasoline-ethanol, diesel/biodiesel or CNG/biomethane blends. It is an environmentally friendly, long life lubricant specifically intended for the latest generation of direct/indirect injection gasoline and diesel (with GPF/DPF) units that command for the very strict VW 508.00/509.00 oil specs. It is also suitable for mild hybrid (diesel-/gasoline-electric) architectures (e.g. VW eTSI units) or engine units requiring a top-tier, low HTHS viscosity ACEA C5 quality level engine oil.

**ACEA C5; API SN Plus; VW 508.00/509.00 (approved), TL 52577; Porsche C20**  
**Level: ACEA A1/B1**

CODE	GRADE/SAE	PACKAGING
JM00108	0W-20	4 X 4L
JM00109	0W-20	12 X1L



## MAGMA SYN M-FE

Extreme fuel economy, low consumption engine oil for the latest generation of gasoline and light duty diesel engines with after-treatment systems (incl. GPF, DPF and TWC). MAGMA SYN M/FE SAE 0W-20 is an environmentally friendly motor oil, specifically engineered to meet the service fill requirements of Mercedes Benz' latest generation hybrid powertrains and Jaguar-Land Rover's high performance gasoline/diesel-powered and gasoline/ethanol-powered standalone ICE units, mild hybrid and plug-in hybrid architectures.

**ACEA C5; MB-Approval 229.71; Jaguar-Land Rover STJLR 51.5122 (approved), STJLR 03.5006**  
**Level: Ford WSS-M12R536-A**

CODE	GRADE/SAE	PACKAGING
JM00208	0W-20	4 X 4L
JM00209	0W-20	12 X1L



## MAGMA SYN V1

Premium quality fully synthetic motor oil of low SAPS technology, specifically formulated for vehicles of the Volkswagen Group requiring a 504.00/507.00 specification. It ensures quick oil circulation, excellent protection against wear and cleanliness of the engine. It minimizes the 'cold start' response time and oil consumption, meets the latest environmental standards and optimises the DPF performance. It is recommended for use in modern VW, Audi, Seat and Skoda gasoline and diesel engines with WIV system for extra-long drain intervals up to 30.000 km (or 2 years). Also suitable for use where an ACEA C2 oil is required. It is backwards compatible with previous VW oil standards 502.00, 505.00, 505.01, 503.00, 503.01, 506.00 or 506.01 (except pre-2006 R5 and V10 engines). It is, also, ideal for BMW and Mercedes Benz vehicles and suitable for engines requiring an oil of API SN or SM performance level.

**SAE 0W-30**  
**ACEA C3; VW 504.00/507.00 (approved), TL 52545; Porsche C30; MB 229.52, MB 229.51; BMW LongLife-04**  
**Level: API SN; FIAT 9.55535.GS1, 9.55535.DS1**

**SAE 5W-30**  
**VW 504.00/507.00 (approved); TL 52195; API SN (approved); ACEA C3; MB 229.51, MB 229.31; BMW LongLife-04; Porsche C30**  
**Level: ACEA C2**

CODE	GRADE/SAE	PACKAGING
JM00901	0W-30	208L
JM00908	0W-30	4 x 4L
JM00909	0W-30	12 x 1L
JM01001	5W-30	208L
JM01002	5W-30	60L
JM01004	5W-30	20L (PAIL)
JM01007	5W-30	4 x 5L
JM01008	5W-30	4 x 4L
JM01009	5W-30	12 x 1L



## MAGMA SYN PSA

Fully synthetic, low SAPS motor oil for modern passenger cars and light commercial vehicles with or without extended service intervals. Specially developed for Peugeot kai Citroen (PSA) turbocharged vehicles with exhaust after-treatment systems following PSA B71 2290 specification requirements. It provides optimum cold starting, lower oil consumption, increased fuel savings (FE ≥ 2,5%) and enhanced sludge and deposit reduction. It is, also, suitable for use in Toyota and FIAT diesel engines requiring a quality oil of ACEA C2 level and for other passenger cars where ACEA A5/B5 or API SN are sought.

**ACEA C2, Peugeot-Citroën PSA B71 2290**  
**Level: Fiat 9.55535.S1**  
**Meets: Honda, Toyota**

CODE	GRADE/SAE	PACKAGING
JM03001	5W-30	208L
JM03004	5W-30	20L (PAIL)
JM03007	5W-30	4 x 5L
JM03008	5W-30	4 x 4L
JM03009	5W-30	12 x 1L





**CERTIFIED  
CYCLON QUALITY**



## MAGMA SYN RNL

A premium, fully synthetic SAE 5W-30 engine oil manufactured using the latest advances in low SAPS additive technology. Tailored to meet engine manufacturers' strict requirements, (e.g. the demanding Renault RN0720 requirements), it provides extremely high levels of protection and cleanliness, improved fuel economy benefits and long drain interval capability. Particularly recommended for Renault Group diesel engines with DPF requiring a RN0720 specification lubricant, it is, also, suitable for use in applications requiring an ACEA C4 level engine oil and Mercedes-Benz models fitted with a Renault diesel engine.

**ACEA C4; Renault RN 0720; MB 226.51**  
**Meets: Dacia, Nissan, Suzuki**

CODE	GRADE/SAE	PACKAGING
JM02501	5W-30	208L
JM02504	5W-30	20L (PAIL)
JM02507	5W-30	4 x 5L
JM02508	5W-30	4 x 4L
JM02509	5W-30	12 x 1L



## MAGMA SYN DXS

Top-tier, low SAPS fully synthetic motor oil designed for Euro 4, 5 & 6 compliant gasoline and diesel engines fitted with diesel particulate filters (DPF), direct injection (DI) and turbocharger. It ensures optimum cold starting, exceptional wear protection and 2.5% fuel economy savings. It is particularly suitable for GM cars demanding dexos2™, engines where GM-LL-B-025 and GM-LL-A-025 oils are recommended and Mercedes Benz BlueTec Diesel engines with SCR post-treatment system demanding a MB 229.52 quality oil. It is intended for use in numerous OEMs such as FIAT, Hyundai/KIA, Ssangyong and Suzuki requiring ACEA C3 or C2 lubricants for extended drain intervals. It satisfies VW's 505.01 specification for diesel engines equipped with low pressure pump injector units (PD).

**API SN (approved); ACEA C2, C3; MB-Approval 229.51, MB-Approval 229.52; Opel-Vauxhall OV0401547; GM dexos2™; VW 505.00/505.01 (approved); BMW LongLife-04**  
**Level: VW 502.00, API CF**

CODE	GRADE/SAE	PACKAGING
JM01501	5W-30	208L
JM01502	5W-30	60L
JM01504	5W-30	20L (PAIL)
JM01507	5W-30	4 x 5L
JM01508	5W-30	4 x 4L
JM01509	5W-30	12 x 1L



## MAGMA SYN TDI

High performance, fully synthetic lubricant based on low SAPS technology, designed for new-generation passenger cars powered by DI turbo diesel or gasoline engines of Euro 4, 5 & 6 emission standards requiring an ACEA C3 engine oil. It is fully compatible with catalytic converters and diesel particulate filters (DPF). Effective anti-wear additives guarantee reliable protection against engine wear and bore polishing. It is particularly applicable for use in high-power gasoline engines, as well as diesel engines of GM (demanding dexos2™), Mercedes Benz (MB 229.51), Volkswagen Group (VW 502.00/505.00/505.01 specifications), BMW (for extended drain intervals) and Porsche, or where SAE 5W-40 oils of ACEA C3 and API SN (or earlier specifications) quality level are recommended.

**API SN (approved), CF; ACEA C3; VW 505.01; MB-Approval 229.51, MB 229.31; BMW LongLife-04; GM dexos2™; Porsche A40**  
**Level: VW 502.00; FIAT 9.55535.S2; Ford WSS M2C-917A**

CODE	GRADE/SAE	PACKAGING
JM02001	5W-40	208L
JM02002	5W-40	60L
JM02004	5W-40	20L (PAIL)
JM02007	5W-40	4 x 5L
JM02008	5W-40	4 x 4L
JM02009	5W-40	12 x 1L



## MAGMA SYN FD

Fully synthetic, extreme fuel economy oil for gasoline-powered passenger and light duty vehicles. Formulated with a very high quality detergent/dispersant additive package, it minimises friction, wear and fuel consumption. It provides for very quick lubrication, excellent "cold start" characteristics, increased drain intervals and a significant fuel saving (FE>of 3.0%) benefit, in addition to the well-sought emissions control (NOx, HC and CO, in particular). Designed with the latest generation Euro 5 Ford EcoBoost engines in mind, it is, also, suitable (backwards compatible) for engines requiring WSS-M2C913-B/C or 925-B oils, as well as for Jaguar, Land Rover and Chrysler/Jeep gasoline engines following Ford specifications (Note: It is NOT suitable for Ford Ka, ST & RS models). It is well-suited for LPG and Euro 5 generation diesel engines requiring a low viscosity ACEA A1/B1 oil.

**API SN (approved); ACEA C5; Ford WSS M2C-948B; Jaguar-Land Rover STJLR.03.5004**  
**Level: ACEA A1/B1; API CF**  
**Meets: Ford (excl. KA, ST, RS models); Chrysler/Jeep (check owner manual)**

CODE	GRADE/SAE	PACKAGING
JM00507	5W-20	4 x 5L
JM00508	5W-20	4 x 4L
JM00509	5W-20	12 x 1L



## MAGMA SYN ULTRA-S

CYCLON MAGMA SYN ULTRA-S is a fully synthetic, advanced fuel economy, low viscosity motor oil, engineered with TriboACT® Formula. It offers maximum performance and wear protection under the most extreme service conditions. Due to its 100% synthetic nature and optimally balanced additive package, it will retain its viscosity and protect gasoline-powered vehicles in situations where more conventional motor oils would be inadequate, e.g. during very cold start environments.

### SAE 0W-20

API SP-RC, SP (approved); SN PLUS (approved); ILSAC GF-6A; GM dexos1TM Gen 2; Ford WSS M2C-947A

Level: API SN Plus-RC, SN-RC; SN, SM, SL, SJ, CF; ILSAC GF-5; GM 6094M  
Meets: Toyota, Lexus, Honda, Nissan, Subaru, Chrysler

### SAE 5W-20

API SP-RC, SP; ILSAC GF-6A; Ford WSS M2C-945A; GM dexos1TM Gen 2  
Level: API SN Plus-RC, SN Plus, SN-RC; SN, SM, SL, SJ, CF; ILSAC GF-5

### SAE 5W-30

API SP-RC, SP (approved); SN Plus (approved); ILSAC GF-6A; GM dexos1TM Gen 2; Ford WSS M2C-946A, WSS M2C-946B1  
Level: API SN Plus-RC, SN-RC; SN, SM, SL, SJ, CF; ILSAC GF-5; Chrysler MS-6395; Honda/Acura HTO-06; GM 4718M

CODE	GRADE/SAE	PACKAGING
JM04701	0W-20	208L
JM04702	0W-20	60L
JM04708	0W-20	4 x 4L
JM04709	0W-20	12 x 1L
JM04801	5W-20	208L
JM04808	5W-20	4 x 4L
JM04809	5W-20	12 x 1L
JM04900	5W-30	1000L
JM04901	5W-30	208L
JM04902	5W-30	60L
JM04908	5W-30	4 x 4L
JM04909	5W-30	12 x 1L



## MAGMA SYN ULTRA

Premium quality and very high performance, synthetic motor oils formulated with an advanced additive system with potential for extended oil drain intervals. They provide for ultimate protection and cleanliness of the engine, viscosity stability for superb high temperature performance, exceptional cold start protection and reduced oil consumption. They are intended for new technology four-stroke, gasoline-/diesel-/LPG-powered engines (incl. those equipped with direct injection, common rail, turbochargers and intercooler) of passenger cars and light duty commercial vehicles. Suitable for extended service intervals or/and severe operating conditions.

### 0W-40

API SN; ACEA A3/B3, A3/B4; VW 502.00, VW 505.00; MB 229.5; Porsche A40, Renault RN 0700, RN 0710

Level: FIAT 9.55535.Z2, 9.55535.M2  
Meets: Nissan

### 5W-30

API SL, CF; ACEA A3/B4; VW 502.00, 505.00; MB 229.5; Renault RN 0710, RN 0700  
Level: API SN; MB 229.3; BMW LongLife-01; FIAT 9.55535.G1; GM LL-B-025, LL-A-025

### 5W-40

API SN (approved), SM, CF; ACEA A3/B4; MB-Approval 229.5, GM LL-B-025; VW 502.00/505.00 (approved); Renault RN 0700, RN 0710; Porsche A40; BMW LongLife-01; Peugeot-Citroën PSA B71 2296

Level: FIAT 9.55535.H2, 9.55535.M2, 9.55535.N2, 9.55535.Z2

CODE	GRADE/SAE	PACKAGING
JM03308	0W-40	4 x 4L
JM03309	0W-40	12 x 1L
JM03500	5W-30	1000L
JM03501	5W-30	208L
JM03502	5W-30	60L
JM03504	5W-30	20L (PAIL)
JM03507	5W-30	4 x 5L
JM03508	5W-30	4 x 4L
JM03509	5W-30	12 x 1L
JM04000	5W-40	1000L
JM04001	5W-40	208L
JM04002	5W-40	60L
JM04004	5W-40	20L (PAIL)
JM04007	5W-40	4 x 5L
JM04008	5W-40	4 x 4L
JM04009	5W-40	12 x 1L
JM04201	5W-40	208L
JM04202	5W-40	60L
JM04209	5W-40	12 x 1L



## MAGMA SYN RC

Racing performance, fully synthetic lubricant, designed to offer ultimate performance and wear protection under the most extreme service conditions to high-output engine units (e.g. WRX/STI, Evo, M Power, etc.). Its synthetic nature combined with the TriboACT® Formula technology enables the creation of a shear-resistant oil film and adequately high oil pressure that guarantee performance and durability. It meets the requirements of Japanese, European and U.S. automakers, such as MB sheet 229.5 and oil industry standards such as API SN or ACEA A3/B4.

API SN, SM, CF; ACEA A3/B4

Level: MB 229.5, MB 229.3; GM LL-B-025; Porsche A40; Renault RN 0710, RN 0700; BMW LongLife-01

CODE	GRADE/SAE	PACKAGING
JM04501	5W-50	208L
JM04507	5W-50	4 x 5L
JM04508	5W-50	4 x 4L
JM04509	5W-50	12 x 1L



CERTIFIED  
CYCLON QUALITY



## MAGMA PRO V1

"Long Life", midSAPS lubricant, suitable for a range of different Euro 4, 5 and 6 petrol and diesel engines with aftertreatment technologies to the highly strict VW 504.00/507.00 oil specifications requirements (backwards compatible with previous VW 502.00, VW 505.00, VW 505.01, VW 503.00, VW 503.01, VW 506.00 & VW 506.01 oil specs). It is highly recommended for service fill use in VW engines equipped with DPF units.

**ACEA C3; API SN**

**Level: ACEA C2; VW 504.00, VW 507.00; MB 229.51; BMW LongLife-04**

**Backwards compatible: VW 502.00, VW 505.00, VW 505.01, VW 503.00, VW 503.01, VW 506.00, VW 506.01**

CODE	GRADE/SAE	PACKAGING
------	-----------	-----------

JM26500	5W-30	1000L
JM26501	5W-30	208L
JM26502	5W-30	60L
JM26504	5W-30	20L (PAIL)
JM26507	5W-30	4 X 5L
JM26508	5W-30	4 X 4L
JM26509	5W-30	12 X 1L



## MAGMA PRO PSA

Low viscosity, synthetic midSAPS engine oil for the lubrication of gasoline and diesel cars equipped with a DPF and TWC, which require a fuel economy oil that satisfies, Peugeot-Citroen, in particular, as well as Toyota, Mazda and FIAT's requirements for higher fuel savings, lower oil consumption and enhanced piston wear protection under demanding operating conditions.

**ACEA C2, A5/B5; API SN Plus, SN**

**Level: Peugeot-Citroën PSA B71 2290; FIAT 9.55535.S1**

**Meets: Honda, Toyota**

CODE	GRADE/SAE	PACKAGING
------	-----------	-----------

JM25500	5W-30	1000L
JM25501	5W-30	208L
JM25507	5W-30	4 X 5L
JM25508	5W-30	4 X 4L



## MAGMA PRO DXS

MidSAPS synthetic lubricant for modern petrol and diesel engines (incl. pump injector ones) fitted with particulate filters. Suitable for use by various OEMs, such as GM, OPEL/Vauxhall, VW, Mercedes Benz, FIAT and others that require an ACEA C3 or C2 quality level lubricant for its superior particulate filter compatibility.

**ACEA C3, C2; API SN Plus, SN, SM, SL**

**Level: VW 505.01, VW 505.00; MB 229.52, MB 229.51; GM dexos2™; BMW LongLife-04**

CODE	GRADE/SAE	PACKAGING
------	-----------	-----------

JM25000	5W-30	1000L
JM25001	5W-30	208L
JM25002	5W-30	60L
JM25004	5W-30	20L (PAIL)
JM25007	5W-30	4 X 5L
JM25008	5W-30	4 X 4L
JM25009	5W-30	12 X 1L



## MAGMA PRO FD5

High performance synthetic, high fuel economy gasoline and diesel engine motor oil. It is specifically designed to surpass Ford's WSS M2C 913D oil specification, being backwards compatible with previous WSS M2C 913C/B/A specifications, it is ideal for passenger vehicle units to be found in various Ford, Jaguar, Mazda models and vehicles that require a high-performance oil of ACEA A5/B5 quality level.

**ACEA A5/B5; API SL, CF**

**Level: Ford WSS M2C-913D; Jaguar-Land Rover STJLR.03.5003; Renault RN 0700;**

**FIAT 9.55535.G1**

**Backwards compatible: Ford WSS M2C-913C, WSS M2C-913B, WSS M2C-913A**

CODE	GRADE/SAE	PACKAGING
------	-----------	-----------

JM26000	5W-30	1000L
JM26001	5W-30	208L
JM26004	5W-30	20L (PAIL)
JM26007	5W-30	4 X 5L
JM26008	5W-30	4 X 4L





## MAGMA SYN F1

Synthetic engine oils of superior performance. Engineered with an innovative additive package, they ensure high levels of engine cleanliness, viscosity retention (and hence "above the top" performance in high temperatures) and outstanding protection during "cold" starts, as well as reduced oil consumption. Due to their excellent dispersant/detergent properties, they are ideal for all modern four-stroke, (in)direct injection, gasoline/diesel/LPG engines of passenger and light duty commercial vehicles, either naturally-aspirated or turbocharged.

### 10W-40

API SN (approved), SM, CF; ACEA A3/B3, A3/B4; VW 505.00; MB-Approval 229.3; Renault RN 0700; JASO MA-2  
Level: VW 502.00

### 15W-40

API SL, CF; ACEA A3/B3, A3/B4; VW 505.00, 501.01; MB 229.1

CODE	GRADE/SAE	PACKAGING
JM13001	10W-40	208L
JM13007	10W-40	4 x 5L
JM13008	10W-40	4 x 4L
JM13009	10W-40	12 x 1L
JM05001	15W-40	208L
JM05007	15W-40	4 x 5L
JM05008	15W-40	4 x 4L
JM05009	15W-40	12 x 1L



## MAGMA HYPER X-200

New generation, premium semisynthetic motor oil series for modern gasoline, higher ethanol gasoline, diesel, LPG and CNG-fueled powertrains. Consisting of very advanced ILSAC GF-6 and API SP performance engine oils, they are ideal for downsized TGD engines as they are formulated to decrease the frequency of low-speed pre-ignition events. They meet or exceed the requirements for Asian, North American, and European vehicles where API service specifications are referenced.

### SAE 5W-30

API SP-RC, SP (approved), SN Plus-RC (approved); ILSAC GF-6A (approved)  
Level: API SN Plus, SN-RC, SN, SM, SL, SJ, CF; ILSAC GF-5

### SAE 5W-40/10W-40

API SP (approved), SN Plus (approved)  
Level: API SN, SM, SL, SJ, CF

CODE	GRADE/SAE	PACKAGING
JM15001	5W-30	208L
JM15002	5W-30	60L
JM15008	5W-30	4 x 4L
JM15009	5W-30	12 x 1L
JM15501	5W-40	208L
JM15502	5W-40	60L
JM15508	5W-40	4 x 4L
JM15509	5W-40	12 x 1L
JM16008	10W-40	4 x 4L



## MAGMA X-100

High performance, advanced, synthetic blend motor oils, developed for gasoline, diesel and LPG engines. They are well-suited to preserve original engine performance thanks to their all-season antiwear properties in severe operating conditions (such as high-rev or/and frequent stop & go city driving). They are suitable for use in fuel-injected, turbocharged or naturally-aspirated, multivalve car engines that run on gasoline, diesel, or LPG. They are highly recommended for numerous passenger cars and light duty commercial vehicles.

### SAE 5W-30/5W-40

API SL, CF; ACEA A3/B3, A3/B4; MB 229.1; VW 501.01, VW 505.00; JASO MA2

### SAE 10W-40

API SL (approved), CF; ACEA A3/B3, A3/B4; MB 229.1; VW 501.01, VW 505.00; JASO MA2

CODE	GRADE/SAE	PACKAGING
JM05501	5W-30	208L
JM05502	5W-30	60L
JM05507	5W-30	4 x 5L
JM05508	5W-30	4 x 4L
JM05509	5W-30	12 x 1L
JM06001	5W-40	208L
JM06002	5W-40	60L
JM06007	5W-40	4 x 5L
JM06008	5W-40	4 x 4L
JM06009	5W-40	12 x 1L
JM06500	10W-40	1000L
JM06501	10W-40	208L
JM06502	10W-40	60L
JM06504	10W-40	20L (PAIL)
JM06507	10W-40	4 x 5L
JM06508	10W-40	4 x 4L
JM06509	10W-40	12 x 1L



CERTIFIED  
CYCLON QUALITY



## MAGMA SUPER

High performance mineral based multigrade oils. They offer excellent oil consumption control and a very high level of engine wear protection. For all naturally-aspirated and turbocharged (in) direct gasoline, diesel or LPG engines of passenger cars, vans and light duty vehicles operating under normal conditions. The high viscosity grades are better-suited suitable for warmer climate countries.

**15W-40**  
API SL (approved), CF; ACEA A3/B3, A3/B4; VW 501.01, 505.00; MB 229.1

**15W-50/20W-50**  
API SL, CF; ACEA A3/B3, A3/B4; VW 501.01, 505.00; MB 229.1; JASO MA2

CODE	GRADE/SAE	PACKAGING
JM07001	15W-40	208L
JM07007	15W-40	4 x 5L
JM07008	15W-40	4 x 4L
JM07009	15W-40	12 x 1L
JM07501	15W-50	208L
JM07508	15W-50	4 x 4L
JM07509	15W-50	12 x 1L
JM08000	20W-50	1000L
JM08001	20W-50	208L
JM08008	20W-50	4 x 4L
JM08009	20W-50	12 x 1L



## MAGMA EXTRA

High performance engine lubricants suitable for use in a wide range of gasoline engines in a variety of applications. It ensures perfect lubrication and wear protection. They are suitable for use in Euro 1, 2, 3 generation gasoline engines in normal operating conditions, providing for a cost efficient, yet high quality lubrication solution. An ideal solution for previous generation North American and Asian models built before 2001.

**API SJ, CF**  
Level: ACEA A2, B2

CODE	GRADE/SAE	PACKAGING
JM08501	15W-40	208L
JM08502	15W-40	60L
JM08504	15W-40	20L (PAIL)
JM08507	15W-40	4 x 5L
JM08508	15W-40	4 x 4L
JM08509	15W-40	12 x 1L
JM09001	20W-50	208L
JM09007	20W-50	4 x 5L
JM09008	20W-50	4 x 4L
JM09009	20W-50	12 x 1L



## MAGMA MULTI

A cost efficient series of engine lubricants, based on a high quality, high viscosity index basestock and an additive package providing for high levels of detergency. Ideal for older technology gasoline vehicles fitted with a carburettor. They meet moderate requirements of certain passenger cars and can be used all-year round.

**API SF, CC**

CODE	GRADE/SAE	PACKAGING
JM09501	15W-40	208L
JM09504	15W-40	20L (PAIL)
JM09507	15W-40	4 x 5L
JM09508	15W-40	4 x 4L
JM09509	15W-40	12 x 1L
JM10001	20W-50	208L
JM10003	20W-50	25L (CAN)
JM10004	20W-50	20L (PAIL)
JM10007	20W-50	4 x 5L
JM10008	20W-50	4 x 4L
JM10009	20W-50	12 x 1L



## MAGMA PRIME

Mineral monograde lubricants with good detergent properties. They protect the metallic surfaces against corrosion, rust and wear. They are suitable for top-up in older gasoline and diesel engines.

**APISC, CC; MIL-L-2104B**

CODE	GRADE/SAE	PACKAGING
JM10501	10W	208L
JM11004	30	20L (PAIL)
JM11008	30	4 x 4L
JM11009	30	12 x 1L
JM11504	40	20L (PAIL)
JM11508	40	4 x 4L
JM11509	40	12 x 1L

# GRANIT

## **COMMERCIAL & HEAVY DUTY DIESEL ENGINE LUBRICANTS** (HDMO)

Lower operating/maintenance costs & extended oil drain intervals; these are today's critical issues for the operator and fleet owner and the challenges that OEMs must address in the most efficient manner. These are exactly the same issues that we put into perspective in order to design and develop our GRANIT series of heavy duty engine oils. On top of all these, we could not possibly neglect an increasingly sought reduction in diesel exhaust emissions and, as a result, our products' full compatibility with the various after-treatment technologies in use.

**In sum, GRANIT series of lubricants will provide up to 3.3% additional fuel economy benefits\*. The overall protection of the engine and turbocharger being critical to owners or operators nowadays, GRANIT oils have been specifically engineered to offer to the engine up to 50% more protection from wear and to the costly turbocharger up to 28% more protection from deposits and sludge.**

**GRANIT engine oils - manufactured in the EU - stand for ultimate reliability at real-life working environments, complete engine, after-treatment system & turbocharger protection and drain intervals extension.**

\*As measured in U.S. EPA's "Smartway" Protocols and SAEJ-1321 for the product GRANIT SYN EURO ULTRA 5W-30.









## GRANIT SYN EURO ULTRA

Top quality, fully synthetic low SAPS engine oil designed for the lubrication of heavy-duty diesel engines compliant to the latest exhaust emission standards Euro IV, Euro V and Euro VI and equipped with DPF, EGR and SCR. It is intended to provide for better fuel economy benefits (of average 1,3%) in the latest Euro VI diesel engines. It is recommended for use in the latest generation turbocharged diesel engines of heavy-duty tractors and buses operating at severe loads and conditions and requiring extended oil drain intervals. It meets the requirements of major European engine manufacturers, such as Mercedes Benz and Volvo, and in particular MAN whose Euro VI engine units demand an oil of MAN 3677 performance level.

**ACEA E9, E6, E7; API CK-4, CJ-4 (approved), SN (approved); MB 228.52, MB 228.51, MB 228.31, MB 235.28; MAN M3775, M3677 (approved), M3271-1; MTU Cat. 3.1; Volvo VDS-4.5 (approved), VDS-4, VDS-3; Renault Trucks RXD, RLD-3 (approved), RLD-2, RGD; Mack EOS-4.5 (approved), EO-O PP, EO-N PP, EO-N, EO-M Plus; Cummins CES 20086; JASO DH-2; Caterpillar ECF-3 (approved); Deutz DQC IV-18LA; Detroit Diesel DFS 93K222; Scania LDF-4; Ford WSS M2C213-A1**  
**Meets: IVECO 18 1804 TLS E9; DAF Extended Drain**

CODE	GRADE/SAE	PACKAGING
JT00501	5W-30	208L
JT00503	5W-30	25L (CAN)
JT00508	5W-30	4 x 4L



## GRANIT SYN EURO MAXX

Fully synthetic, low SAPS, ultra high performance diesel (UHPD) engine oil. It is recommended for the latest low emission, Euro IV, V & VI heavy duty engines fitted with exhaust after treatment devices (incl. DPF). It provides the highest levels of protection for the engine, the turbocharger and the exhaust after-treatment system. It exceeds the requirements of all major European manufacturers while it can also be used for older Euro II, III engines or engines running on natural gas (CNG) (such as Mercedes Benz, MAN and Volvo).

**ACEA E6, E9, E7; API CI-4 (approved); MAN M3477, M3271-1; MB-Approval 228.51; Volvo VDS-3 (approved); Renault VI RGD, RXD, RLD-2 (approved); Mack EO-N (approved); MTU Cat. 3.1 (approved); Deutz DQC IV-18 LA; Cummins CES 20077, CES 20077; JASO DH-2, Cat ECF-1a**  
**Meets: DAF**

CODE	GRADE/SAE	PACKAGING
JT01000	10W-40	1000L
JT01001	10W-40	208L
JT01002	10W-40	60L
JT01003	10W-40	25L (CAN)
JT01004	10W-40	20L (PAIL)
JT01008	10W-40	4 x 4L



## GRANIT SYN EURO DXL

A fully synthetic, ultra high performance oil (UHPDO) specially engineered for diesel powertrains operating under extreme conditions. The high performance additives used enable the final product complying with the latest requirements of all major European OEMs (such as Mercedes Benz and Scania) regarding piston cleanliness, excellent control of bore polish and valve train wear and thus it is essential for longer engine life. It meets the requirements of most European manufacturers for Euro III/IV engines and certain Euro V and, in particular, Scania Euro VI applications with exhaust gas recirculation (EGR) or/and selective catalytic reduction (SCR) systems. Suitable for a wide range of transportation applications for which maximum allowable change intervals are enabled.

**ACEA E4, E7; API CF; MB 228.5, MB 235.28; MAN M3277; Volvo VDS-3; MTU Cat. 3; Renault VI RXD, RLD-2; Scania LDF-3; DAF Extended Drain; Cummins CES 20077; VOITH Retarder Oil Class B; Deutz DQC IV-10; Mack EO-N; IVECO 18-1804 TFE**

CODE	GRADE/SAE	PACKAGING
JT01000	5W-30	208L
JT01503	5W-30	25L (CAN)



## GRANIT SYN EURO FLEET

SYN EURO FLEET SAE 10W-40 is a fully synthetic, top-tier, heavy duty diesel engine oil designed to deliver performance reserves in demanding industry and OEM specifications and to offer extended long drains. It provides outstanding protection from bore polishing and deposit build-up. It is suitable for all types of on-road and off-road heavy duty engines that require performance levels as defined by API CI-4, ACEA E4, ACEA E7 and MB 228.5 or SCANIA LDF-2, providing exceptional performance and advanced protection of the EGR and SCR systems.

**API CI-4 (approved); ACEA E4, E7; MB-Approval 228.5; MAN M3277 (approved); Volvo VDS-3 (approved); MTU Cat. 3 (approved); Renault VI RXD, RLD-2 (approved); Scania LDF-2 (approved); Deutz DQC III-10; DAF Extended Drain; Cummins CES 20077, CES 20078; Mack EO-N (approved), EO-M Plus; IVECO 18-1804 T3 E4**

CODE	GRADE/SAE	PACKAGING
JT02000	10W-40	1000L
JT02001	10W-40	208L
JT02003	10W-40	25L (CAN)
JT02004	10W-40	20L (PAIL)





CERTIFIED  
CYCLON QUALITY



## GRANIT VDS

Superior performance SHPD, midSAPS heavy duty engine oil exceeding the requirements of the strict VDS-4 long drain specification for the latest generation turbo-charged Volvo engines with/without DPF. Formulated with highly hydrotreated base oils, it provides for excellent soot handling, wear and oxidation resistance. It is suitable for engines fitted with particulate filters that operate in very severe operating conditions. It can be used in both on-road Euro IV, V, VI, EPA 2007/2010 units and off-highway stage IIIB and Tier IV engines that require performance levels as defined by API CK-4/CJ-4, API SM and ACEA E9/E7 sequences and run on low sulphur fuel (<15ppm). An extremely versatile HDEO being equally suitable for older generation Euro II and III engines that 'run' on higher sulphur (up to 500ppm) diesel fuel.

### SAE 10W-30

ACEA E9, E7; API CK-4; Caterpillar ECF-3; MB 228.31; MAN M3775; MTU Cat. 2.1, Volvo VDS-4.5; Mack EOS-4.5; Renault Trucks RLD-4; Deutz DQC III-10 LA; Detroit Diesel DFS 93K222; Cummins CES 20086

### SAE 10W-40

API CK-4 (approved), CJ-4, CI-4+ (approved), CI-4, SM; ACEA E9, E7; MB 228.31; Volvo VDS-4 (approved); MAN M3775, M3575; MTU Cat. 2.1; Mack EO-O Premium Plus (approved); Renault Trucks RLD-3 (approved); Caterpillar ECF-3, ECF-2, ECF-1a; Cummins CES 20081; Detroit Diesel DFS 93K218; Deutz DQC III-10 LA; Global DHD-1 Level: JASO DH-2

### SAE 15W-40

API CK-4 (approved), CJ-4, CI-4+ (approved), CI-4, SM, SN (approved); ACEA E9, E7; MB-Approval 228.31; MAN M3775, M3575; MTU Cat. 2.1; Mack EO-O Premium Plus (approved); Renault Trucks RLD-3 (approved); Volvo VDS-4 (approved); Caterpillar ECF-3, ECF-2, ECF-1a; Cummins CES 20081; Detroit Diesel DFS 93K218; Deutz DQC III-10 LA; Global DHD-1 Level: JASO DH-2

CODE	GRADE/SAE	PACKAGING
JT02601	10W-30	208L
JT02604	10W-30	20L (PAIL)
JT02401	10W-40	208L
JT02404	10W-40	20L (PAIL)
JT02500	15W-40	1000L
JT02501	15W-40	208L
JT02504	15W-40	20L (PAIL)



## GRANIT SHPD PLUS

Premium quality, fully synthetic, super high performance diesel engine oil series meeting the requirements of advanced diesel engines equipped with exhaust gas recirculation system (EGR) or selective catalytic reduction (SCR) systems. It enables reliable performance concerning soot-induced wear and easy cold starts. GRANIT SYN SHPD PLUS SAE 10W-40 carries a wide range of OEM approvals, making it an ideal lubricant for mixed fleet operators. It is recommended for highly-rated diesel engines in commercial vehicles, trucks, buses and equipment in road construction and even agricultural applications meeting Euro I, Euro II, Euro III, Euro IV and Euro V emission standards and running under demanding conditions of mid to long drain intervals. It is also suitable for passenger/light duty commercial vehicles that require an ACEA B4 or API SL performance oil.

ACEA E7, E5, E3, A3/B3, A3/B4; API CI-4 (approved), CH-4, CG-4, SL (approved); MB-Approval 228.3, MB-Approval 229.1; Global DHD-1; MAN M3275-1; MTU Cat. 2; Volvo VDS-3 (approved); Renault Trucks RLD-2 (approved); Mack EO-M Plus, EO-N (approved); Cummins CES 20076, CES 20077, CES 20078; DAF SHPD; Caterpillar ECF-2, ECF-1a; Deutz DQC III-10; Detroit Diesel DFS 93K215  
Level: Allison C4; ZF TE-ML 07C

CODE	GRADE/SAE	PACKAGING
JT03000	10W-40	1000L
JT03001	10W-40	208L
JT03002	10W-40	60L
JT03004	10W-40	20L (PAIL)
JT03008	10W-40	4 x 4L



## GRANIT SYN SHPD

GRANIT SYN SHPD SAE 15W-40 is a synthetic, mixed fleet diesel engine oil designed to provide excellent protection for fleets of commercial vehicles. It is approved by major global vehicle manufacturers for use in Euro V, IV and Euro III generation European, US and Japanese technology vehicles. It fights corrosion- and soot-induced wear, the primary concern for Euro IV/V clean technology engines in much tougher environments because of the increased use of biodiesel. It is a truly versatile product, which can be used in trucks, buses, LCVs, off-road vehicles, agricultural and construction equipment, as well as in light-duty diesel and gasoline engines requiring an ACEA A3/B4 or/and API SL oil.

ACEA E7, E5, E3, A3/B3, A3/B4; API CI-4 (approved), CH-4, CG-4, SL (approved); MB 228.3, MB 228.1, MB 229.1; Global DHD-1; MAN M3275-1; MTU Cat. 2; Volvo VDS-3 (approved); Renault VI RLD-2 (approved); Mack EO-M Plus, EO-N (approved); Cummins CES 20076, CES 20077, CES 20078; DAF SHPD; Caterpillar ECF-2 (approved), ECF-1a; Deutz DQC III-10; Detroit Diesel DFS 93K215; IVECO 18-1804 T2 E3  
Level: Allison C4; ZF TE-ML 07C

CODE	GRADE/SAE	PACKAGING
JT03500	15W-40	1000L
JT03501	15W-40	208L
JT03503	15W-40	25L (CAN)
JT03504	15W-40	20L (PAIL)
JT03508	15W-40	4 x 4L
JT03509	15W-40	12 x 1L





## GRANIT SYN HPD

GRANIT SYN HPD is a premium quality, synthetic, super high performance diesel engine oil meeting the requirements of advanced diesel engines equipped with exhaust gas recirculation system (EGR) or selective catalytic reduction (SCR) systems. It demonstrates great oxidation resistance, resistance to shearing and very low oil consumption. It is particularly suitable for all Euro II, III and most Euro IV & V diesel engines (without DPF), either normally-aspirated or highly-rated, turbocharged ones, operating under high temperature conditions in highway and off-highway applications, such as mining, quarrying, agricultural and construction machinery.

**ACEA E7, E5, E3, A3/B3, A3/B4; API CI-4, CH-4, CG-4, SL; MB 228.3; Global DHD-1 Level; Volvo VDS-3; MAN M3275; Renault VI RLD-2; Mack EO-M Plus; Deutz DQC III-10; MTU Cat. 2; Cummins CES 20076, CES 20077, CES 20078; DAF SHPD; Caterpillar ECF-2, ECF-1a; ZF TE-ML 07C; Detroit Diesel DFS 93K215; Allison C4**

CODE	GRADE/SAE	PACKAGING
JT04001	20W-50	208L
JT04003	20W-50	25L (CAN)
JT04004	20W-50	20L (PAIL)
JT04008	20W-50	4 x 4L
JT04009	20W-50	12 x 1L
JT04016	20W-50	18L (PAIL)



## GRANIT MAXIMUM

A high quality, super high performance diesel engine oil that meets the requirements of advanced diesel engines equipped with exhaust gas recirculation system (EGR) or selective catalytic reduction (SCR) systems. It is engineered to provide reliable performance, advanced soot and wear control and low oil consumption. It is suitable for all Euro II, III and most Euro IV & V diesel engines (without DPF) of mid to long drain intervals, either normally-aspirated or highly-rated, turbocharged ones, operating under severe conditions. It is the ideal choice for heavy-duty, demanding operating environments (off-highway), international transport vehicles (TIR) and buses. It is strongly recommended for vehicles that operate in a wide temperature range.

**ACEA E7, E5, E3; API CI-4 (approved), CH-4, CG-4, SL (approved); MB-Approval 228.3; MAN M3275-1; MTU Cat. 2 (approved); Volvo VDS-3 (approved); Renault VI RLD-2 (approved); Mack EO-M Plus, EO-N (approved); Global DHD-1; Cummins CES 20076, CES 20077, CES 20078; DAF SHPD; Allison C4; Caterpillar ECF-2, ECF-1 (approved); ZF TE-ML 07C; Deutz DQC III-10; Detroit Diesel DFS 93K215; IVECO 18-1804 T2 E3**

CODE	GRADE/SAE	PACKAGING
JT04501	15W-40	208L
JT04502	15W-40	60L
JT04503	15W-40	25L (CAN)
JT04504	15W-40	20L (PAIL)
JT04506	15W-40	10L (PAIL)
JT04507	15W-40	4 x 5L
JT04508	15W-40	4 x 4L
JT04509	15W-40	12 x 1L



## GRANIT MAXIMUM XTB

Very high performance diesel engine oil for severe commercial (on-/off-road) applications, specifically formulated for heavy duty diesel engines - equipped with exhaust gas recirculation (EGR) or/and selective catalytic reduction (SCR) aftertreatment technologies. Boosted with an advanced antiwear and increased detergent additive chemistry, it is suitable for all Euro II, III and most Euro IV and V generation diesel units (without DPF) providing for complete treatment and enhanced drain intervals. It is the ideal choice for demanding operating environments and for engines that operate on higher sulphur fuels and a wide temperature range.

**ACEA E7, E5; API CI-4 Plus, CI-4, CH-4, CG-4, CF-4; MAN 3275-1; MB 228.3, 228.1; MTU Cat.2; Global DHD-1; Cummins CES 20076, CES 20077, CES 20078; Deutz DQC III-10**

CODE	GRADE/SAE	PACKAGING
JT04401	15W-40	208L
JT04404	15W-40	20L (PAIL)



## GRANIT SUPER

CYCLON GRANIT SUPER SAE 20W-50 is a super high performance diesel engine oil suitable for all Euro II, III and most Euro IV & V diesel engines of mid to long drain intervals, equipped with exhaust gas recirculation system (EGR) or selective catalytic reduction (SCR) systems. It prevents deposits formation and provides exceptional protection to bearings and 'yellow metals' from corrosion. The creation of a strong oil film retains lubrication and cleanliness to engine parts in harsh operating conditions such as the turbine shaft area. It is the ideal choice for heavy-duty, demanding operating environments (off-highway), international transport vehicles (TIR) and buses.

**ACEA E7, E5, E3; API CI-4 (approved), CH-4, CG-4, CF-4, SL (approved); MB 228.3; Global DHD-1 Level; MAN M3275-1; MTU Cat. 2; Volvo VDS-3; Renault VI RLD-2; Mack EO-M Plus; Cummins CES 20076, CES 20077, CES 20078; DAF SHPD; Caterpillar ECF-2, ECF-1a; Deutz DQC III-10; Detroit Diesel DFS 93K21 5; Allison C4**

CODE	GRADE/SAE	PACKAGING
JT05000	20W-50	1000L
JT05001	20W-50	208L
JT05003	20W-50	25L (CAN)
JT05004	20W-50	20L (PAIL)
JT05007	20W-50	4 x 5L
JT05008	20W-50	4 x 4L
JT05009	20W-50	12 x 1L
JT05016	20W-50	18L (PAIL)



CERTIFIED  
CYCLON QUALITY



## GRANIT EXTRA

High performance, universal engine lubricant suitable for use in a wide range of diesel and gasoline engines in a variety of applications. It is produced according to the latest technological developments and ensures perfect lubrication and wear protection. It is suitable for use in mixed fleets of naturally-aspirated and turbocharged Euro I, II, III diesel and gasoline engines burning low or medium sulphur fuel, and in both on-/off-highway fleet operations under normal operating conditions for cost effective lubrication.

**API CF-4, CG-4, SG, SJ; ACEA E2; MB 228.1; MTU Cat. 1; Volvo VDS; MAN 271 Level: ACEA A2, B2**

CODE	GRADE/SAE	PACKAGING
JT05500	15W-40	1000L
JT05501	15W-40	208L
JT05502	15W-40	60L
JT05504	15W-40	20L (PAIL)
JT05506	15W-40	10L (PAIL)
JT05507	15W-40	4 x 5L
JT05508	15W-40	4 x 4L
JT05509	15W-40	12 x 1L
JT06000	20W-50	1000L
JT06001	20W-50	208L
JT06004	20W-50	20L (PAIL)
JT06007	20W-50	4 x 5L
JT06008	20W-50	4 x 4L
JT06009	20W-50	12 x 1L



## GRANIT MULTI

High quality multigrade lubricants formulated to meet moderate requirements of certain commercial vehicles. They can be used all year round in naturally- aspirated or turbocharged indirect injection diesel engines. Also suitable for gasoline vehicles fitted with a carburettor.

**API CD, SF; CCMC D2, G2, PD-2; MIL-L-46152B**

CODE	GRADE/SAE	PACKAGING
JT06501	15W-40	208L
JT06504	15W-40	20L (PAIL)
JT06506	15W-40	10L (PAIL)
JT06507	15W-40	4 x 5L
JT06508	15W-40	4 x 4L
JT06509	15W-40	12 x 1L
JT07000	20W-50	1000L
JT07001	20W-50	208L
JT07003	20W-50	25L (CAN)
JT07004	20W-50	20L (PAIL)
JT07006	20W-50	10L (PAIL)
JT07007	20W-50	4 x 5L
JT07008	20W-50	4 x 4L
JT07009	20W-50	12 x 1L



## GRANIT PRIME

High quality monograde lubricants for four-stroke diesel and gasoline engines. They ensure total protection and high performance under any operating condition. Suitable for high-output diesel and petrol engines, either naturally aspirated or turbocharged ones, in on-/off-highway applications and agricultural equipment. They are also suitable for use in powershift transmissions, torque converters and hydraulic systems, if recommended by the manufacturer. They are ideal for stationary engines. The grades SAE 30 and 40 are, also, suitable for two-stroke engines require API CF-2 oil.

**API CF, CF-2, SJ; ACEA E2; MAN 270; MB 228.0; Allison C-4; MTU Cat. 1; Caterpillar TO-2**

CODE	GRADE/SAE	PACKAGING
JT07501	10W	208L
JT07504	10W	20L (PAIL)
JT08001	20W	208L
JT08004	20W	20L (PAIL)
JT08500	30	1000L
JT08501	30	208L
JT08504	30	20L (PAIL)
JT08508	30	4 x 4L
JT08509	30	12 x 1L
JT09000	40	1000L
JT09001	40	208L
JT09004	40	20L (PAIL)
JT09008	40	4 x 4L
JT09009	40	12 x 1L
JT09501	50	208L
JT09504	50	20L (PAIL)



## GRANIT S-3

High quality monograde lubricants. They contain detergents able to neutralize the strong acids produced by fuel of high sulphur content. They protect engine against wear and corrosion. They are used whenever quality of API CD level is sought, such as old technology, normally-aspirated or turbo diesel and gasoline engines in mining, construction, marine, other stationary and agricultural applications.

**API CD, SF; CCMC D2, G2, PD-2; MIL-L-2104E, MIL-L-46152B; Caterpillar TO-2**

CODE	GRADE/SAE	PACKAGING
JT10001	10W	208L
JT10004	10W	20L (PAIL)
JT10500	30	1000L
JT10501	30	208L
JT10504	30	20L (PAIL)
JT10506	30	10L(PAIL)
JT11000	40	1000L
JT11001	40	208L
JT11004	40	20L (PAIL)
JT11006	40	10L(PAIL)
JT11007	40	4 x 5L
JT11501	50	208L
JT11504	50	20L (PAIL)
JT11507	50	4 x 5L
JT11508	50	4 x 4L
JT11509	50	12 x 1L



## GRANIT NATGAS SP

High performance, low ash lubricant oil. Designed for high output naturally- aspirated and turbocharged engines in stationary applications fuelled by natural gas. Suitable for use in engines equipped with catalytic exhaust systems. They can be used for extended drain intervals. Exceed the requirements of Waukesha, MWM Deutz, Caterpillar Wäertsilä, Jenbacher, MDE, MAN B&W, Guascor, Dresser-Rand, Ulstein Bergen..

**Level: API CD**

CODE	GRADE/SAE	PACKAGING
JM13601	40	208L



## D SUPER LM

High performance and high alkalinity, zinc-/chlorine-free lubricant for medium-speed engines operating on distillate fuels, biodiesel and LNG, and in heavy duty shore/offshore environments. It has been engineered with advanced low-ash, phosphorus-free chemistry, specifically, for General Electric and Electro-Motive Division medium-speed engines. It delivers proven wear protection in EPA Tier IV and LMOA Gen. 5 engines while it ensures the optimum protection of previous generation engines. It is, particularly, recommended for the lubrication of two-/four-stroke, diesel-electric or diesel engines that are to be found in demanding marine, rail or power generation applications.

**Electro-Motive Diesel (EMD) LMOA Generation 5; General Electric LMOA Generation 4 Long Life**

**Level: API CF, CF-2**

**Meets: Caterpillar 3600 Series, Alco, Detroit Diesel 149 Series, Fairbanks Morse**

CODE	GRADE/SAE	PACKAGING
Jl43004	40	20L (PAIL)
Jl43031	40	180Kgr





CERTIFIED  
CYCLON QUALITY



## ERGON

Specially designed to meet in full the performance characteristics of Caterpillar's TO-4 specification. They deliver superior friction properties, anti-wear protection, full seal and metal compatibility and very good oxidation stability. To be used in power shift transmissions, differentials, final drives, clutches and hydraulic systems of Caterpillar's newer and older models and in any other equipment, such as tractors, construction machinery and farming machinery where an oil of TO-4 and Allison C-4 specifications is sought.

**API CF, CF-2; Caterpillar TO-4; Komatsu KES 07.868.1; Allison C-4; ZF TE-ML 03C**

CODE	GRADE/SAE	PACKAGING
JA02500	10W	1000L
JA02501	10W	208L
JA02504	10W	20L (PAIL)
JA03000	30	1000L
JA03001	30	208L
JA03004	30	20L (PAIL)
JA03501	50	208L
JA03504	50	20L (PAIL)



**GRANIT**



## FARMA FLUIDE 10W30

Super universal oil (STOU) for all agricultural equipment. Blended from highly refined mineral oils and carefully selected additives for the reliable lubrication of agricultural tractors and ancillary farm machinery. Suitable for use in all turbocharged or naturally-aspirated diesel engines working under the most severe conditions, in mechanical transmissions, hydraulic systems, wet brakes and/or immersed clutches. Exceeds the requirements of Massey Ferguson, John Deere, Ford New Holland, FIAT, Zetor, Landini, Lamborghini etc.

**API CG-4, CF-4, CF, SF, GL-4; ACEA E3; Allison C-4; Caterpillar TO-2; Massey Ferguson M-1135, M-1139, M-1143, M-1144, M-1145; ZF TE-ML 06A, TE-ML 06B, TE-ML 06C, TE-ML 07B; Ford New Holland 82009201, 82009202, 82009203; Ford WSS M2C-159B, WSS M2C-159C, WSS M2C-134D, WSS -86B, WSS-86C; John Deere J20C, J20D, J27; Case New Holland MAT 3525, MAT 3526; Case IH MS-1204, MS-1206, MS-1207, MS-1209; Vickers M-2950-S, I-286-S**

**Meets: Sauer Sunstrand/Danfoss (HydroStatic Trans Fluid)**

CODE	GRADE/SAE	PACKAGING
JA00501	10W-30	208L
JA00502	10W-30	60L
JA00504	10W-30	20L (PAIL)
JA00508	10W-30	4 x 4L



## FARMA PRIME 20W30

Super universal oil (STOU) for all agricultural equipment. Blended from highly refined mineral oils and carefully selected additives for the reliable lubrication of agricultural tractors and ancillary farm machinery. Suitable for use in all turbocharged or naturally-aspirated diesel engines working under the most severe conditions, in mechanical transmissions, hydraulic systems, wet brakes and/or immersed clutches. Exceeds the requirements of Massey Ferguson, John Deere, Ford New Holland, FIAT, Zetor, Landini, Lamborghini etc.

**API CG-4, CF-4, CF, SF, GL-4; ACEA E3; Allison C-4; Caterpillar TO-2; Massey Ferguson M-1135, M-1139, M-1143, M-1144, M-1145; ZF TE-ML 06A, TE-ML 06B, TE-ML 06C, TE-ML 07B; Ford New Holland 82009201, 82009202, 82009203; Ford WSS M2C-159B, WSS M2C-159C, WSS M2C-134D, WSS-86B, WSS-86C; John Deere J20C, J20D, J27; Case New Holland MAT 3525, MAT 3526; Case IH MS-1204, MS-1206, MS-1207, MS-1209; Vickers M-2950-S, I-286-S**

**Meets: Sauer Sunstrand/Danfoss (HydroStatic Trans Fluid)**

CODE	GRADE/SAE	PACKAGING
JA01000	20W-30	1000L
JA01001	20W-30	208L
JA01004	20W-30	20L (PAIL)



## FARMA 15W40

Super universal oil (STOU) for all agricultural equipment. Blended from highly refined mineral oils and carefully selected additives for the reliable lubrication of agricultural tractors and ancillary farm machinery. Suitable for use in all turbocharged or naturally-aspirated diesel engines working under the most severe conditions, in mechanical transmissions, hydraulic systems, wet brakes and/or immersed clutches. Exceeds the requirements of Massey Ferguson, John Deere, Ford New Holland, FIAT, Zetor, Landini, Lamborghini etc.

**API CG-4, CF-4, CF, SF, GL-4; ACEA E3; Allison C-4; Caterpillar TO-2; Massey Ferguson M-1135, M-1139, M-1143, M-1144, M-1145; ZF TE-ML 06A, TE-ML 06B, TE-ML 06C, TE-ML 07B; Ford New Holland 82009201, 82009202, 82009203; Ford WSS M2C-159B, WSS M2C-159C, WSS M2C-134D, WSS-86B, WSS-86C; John Deere J20C, J20D, J27; Case New Holland MAT 3525, MAT 3526; Case IH MS-1204, MS-1206, MS-1207, MS-1209; Vickers M-2950-S, I-286-S**

**Meets: Sauer Sunstrand/Danfoss (HydroStatic Trans Fluid)**

CODE	GRADE/SAE	PACKAGING
JA01501	15W-40	208L
JA01504	15W-40	20L (PAIL)





CERTIFIED  
CYCLON QUALITY



## FARMA UTTO 10W30/80W

FARMA UTTO is a low viscosity SAE 80W (or SAE 10W30) universal tractor transmission fluid intended for use in all agricultural machinery and many off-road applications. It is carefully formulated by high quality base oils and special additives offering superior friction performance. It eliminates the chatter in wet brakes and provides excellent shift performance in powershift transmissions resulting in reduced operating fatigue. FARMA UTTO is suitable for mechanical transmissions, power steering systems, PTOs, hydraulic systems, wet brakes or/and immersed brake clutches of agricultural (all tractor types, combine harvesters, sprayers), construction, forestry and handler equipment. FARMA UTTO can be used in applications requiring API GL-4 of SAE 80W grade lubricants in all gear applications except hypoid gear designs.

**API GL-4; Case IH MS-1204, MS-1206, MS-1207, MS-1209, MS-1210, MS-1216, MS-1230 (Poclair), MS-1317, MS-143, MS-144, MS-145 (TCH Fluid), MS-185 (TFD Fluid); Case New Holland MAT 3525, MAT 3526, MAT 3505, MAT 3510, MAT 3540; Ford New Holland FNHA-2-C-200.00, FNHA-2-C-201.00, M4864A, M4864B; Ford M2CA-C, ESN M2C-41, ESN M2C-41A, ESN M2C-41B, ESN M2C-43, ESN M2C-48B, ESN M2C-48C, ESN M2C-53A, ESN M2C-53B, ESN M2C-77A, ESN M2C-78A, ESN M2C-79A, ESN M2C-86A, ESN M2C-86B, WSS M2C-86C, ESN M2C-92A, ESN M2C-134D, ESN M2C-142A, ESN M2C-143, ESN M2C-159A, ESN M2C-159C; New Holland NH 410B; John Deere J20D, J20C, J20B, J20A, J14C, J14A, J21A; Massey Ferguson M-1145 (M-1135, M-1141, M-1143), M-1138, M-1129, M-1129A, M-1127, M-1127A, M-1127B, M-1110, M-1103A, M-1103B; Volvo WB101/97303 (STD 1273,03) (approved); ZF TE-ML 03E, TE-ML 05F; JCMAS HK P041, HK P042; Caterpillar TO-2; Allison C-4, C-3, C-2; Kubota UDT, Super UDT, Super UDT2; Komatsu KES 07.866, KES 07.868.1; DIN 51524 Part 2 HLP; Denison (Parker) HF-0, HF-2, HF-1; AFNOR NF E48-603 HM; Vickers M-2950-S, I-286-S; Eaton 35VQ25**  
**Meets: Komatsu AXO80; Case IH Hy-Tran B-6; Case-O-Matic Type A; Sauer Sunstrand/Danfoss (HydroStatic Trans Fluid); AGCO Permatran 821XL; Powerfluid 821XL; FIAT Hesston AF-87; Deutz Allis Power Fluid 821XL, 25741, 25743, 246634, 272843; Landini; Dresser; IMT**


CODE	GRADE/SAE	PACKAGING
JA02000	80W	1000L
JA02001	10W-30/80W	208L
JA02002	80W	60L
JA02004	10W-30/80W	20L (PAIL)
JA02006	10W-30/80W	10L (PAIL)
JA02008	10W-30/80W	4 x 4L



FARMA



**LAVA**

 **MOTORCYCLE &  
OUTBOARD  
ENGINE LUBRICANTS**  
(MOTO)

Population increase in large urban centers and the consequent increase of cars are responsible for the exponentially increased driving congestion in city roads. As a way out of this bottleneck, a substantial percentage of daily commuters turned their attention to bikes and scooters for their daily routine and for their ease of mind. The comprehensive line of LAVA motorcycle engine oils was developed to accommodate the motorcyclists that need to drive their bike on a daily basis and subject their 2- or 3-wheeler to frequent "stop n' drive", gear shifting and turning.

**LAVA motorcycle engine oils - manufactured in the EU - stand for ultimate engine protection and reliability, but not at the expense of performance.**











## LAVA SYN RACING 4T

Fully synthetic, multigrade, four-stroke engine lubricant, intended for use in high performance racing bikes. Its unique formula enables premium lubrication performance and wet clutch utilization under extreme conditions of shearing and temperatures. It secures maximum power performance, increased acceleration and virtually no oil loss. It covers the requirements of leading motorcycle manufacturers Honda, Suzuki, Yamaha, Kawasaki, etc. Suitable for use in high output/high rpm's four-stroke motorcycles, such as competition or enduro bikes and in any on-/off-road applications.

**API SL; JASO MA2**

CODE	GRADE/SAE	PACKAGING
JL03502	10W-40	60L
JL03508	10W-40	4 x 4L
JL03509	10W-40	12 x 1L



## LAVA SYN 4T

Fully synthetic multigrade lubricant for four-stroke motorcycles' engines. It exceeds API SL and JASO specifications. It ensures smooth wet clutch and gear box operation. It shows strong resistance to thermal breakdown for excellent operation in high loads/rpm's and meets major OEM' demands, such as Honda, Suzuki, Yamaha, Kawasaki, BMW, etc. Suitable for modern four-stroke engines, large mono- & twin-cylinder, on-/off-road bikes with air-cooled engines. It is, also, suitable for the majority of classic motorbikes requiring a product with a strong resistance to evaporation.

**API SL; JASO MA2, MA**

CODE	GRADE/SAE	PACKAGING
JL04002	15W-50	60L
JL04009	15W-50	12 x 1L



## LAVA FSA 4T

Premium quality motor oil for 4-stroke motorcycles, scooters and mopeds. It is suitable for street, on-/off-road, enduro motorcycles including multi-valve, V-Twin air or water-cooled engines running on any type of fuel. It meets the optional requirements of all leading engine manufacturers.

**API SL; JASO MA2, MA**

CODE	GRADE/SAE	PACKAGING
JL06000	10W-40	1000L
JL06019	10W-40	12 X 0,8L
JL06500	20W-50	1000L
JL06519	20W-50	12 X 0,8L



## LAVA SUPER 4T

Multigrade lubricant for four-stroke motorcycles. It provides high protection against wear in engines and transmissions in high speeds and high temperatures and extends the life of the engine. It is suitable for all types of motorcycles and recommended for a wide range of bikes and large-sized scooters with wet clutches. It is particularly well-suited for urban "stop n' go" riding conditions.

**API SG; JASO MA2, MA**

CODE	GRADE/SAE	PACKAGING
JL04502	20W-50	60L
JL04509	20W-50	12 x 1L





CERTIFIED  
CYCLON QUALITY



## LAVA SYN 2T



A premium quality, fully synthetic lubricant for high performance two-stroke motorcycle engines. It provides superior lubricity for minimal friction wear, clean burning for low smoke while the strong detergency properties eliminate the accumulation of gum deposits in rings area, in the exhaust port system and in spark plugs. Particularly suitable for two-stroke air-cooled or water-cooled engines operating under high loads and high rpm's, such as racing, enduro and other on-/off-road applications. Exceeds the most stringent demands of global OEM such as Suzuki, Honda, Yamaha, Husqvarna and Stihl. It is suitable for premix or injection lubrication systems. The suggested dilution ratio is 1:50 (parts of lubricant in parts of fuel) or 2%.

**JASO FD, FC; API TC; ISO 6743-15 (ISO-L-EGC, ISO-L-EGD); TISI; Piaggio Hexagon**

CODE	GRADE/SAE	PACKAGING
JL02009	—	12 x 1L

## LAVA 2T SCOOTER



High performance, smokeless lubricant for two-stroke engines. It is a clean burning product creating a strong oil film on all metal surfaces protecting them from wear and corrosion. It contains special dispersant additives that minimize the varnish and deposit formation. It improves power and extends engine life. Compatible with modern catalytic converters. It is suitable for two-stroke motorcycles and scooters operating over a wide range of loads and rpm's as in "stop-start" city driving. It is suitable for motorcycles with premix or injection oil systems at a suggested dilution (in fuel) ratio of 2%.

**API TC; ASTM TSC-3; JASO FC; TISI; ISO 6743-15 (ISO-L-EGD)**

CODE	GRADE/SAE	PACKAGING
JL03009	—	12 x 1L

## LAVA 2T SUPER MIX



Low smoke lubricant for use in air-/water-cooled two-stroke motorcycles of low capacity and low performance. It is suitable for premix and injection oil systems. The suggested dilution ratio is 2%. For all types of two-stroke motorcycle engines of all displacements such as motorcycles, scooters, mopeds. To be mixed with gasoline at a ratio as recommended by the manufacturer.

**API TA, TB; JASO FB; ISO 6743-15 (ISO-L-EGB)**

CODE	GRADE/SAE	PACKAGING
JL02501	—	208L
JL02504	—	20L (PAIL)
JL02509	—	12 x 1L
JL02515	—	70 x 200ML

## LAVA CYBIO-OB 2T



Ashless, solvent-free, biodegradable, top performance synthetic ester-based engine oil, intended for use in marine outboard two-stroke engines. It meets the European Ecolabel requirements and may be used in environmentally sensitive areas. Specifically engineered to deliver high deposit control in conventional outboard engines, enhanced filterability that minimises filter blockages, hence assisting in lower maintenance costs. It is suitable for outboards, land-use two-stroke engines and chainsaws.

**NMMA TC-W3  
Meets: EU Ecolabel criteria**

CODE	GRADE/SAE	PACKAGING
JL01004	—	20L (PAIL)
JL01008	—	4 x 4L
JL01009	—	12 x 1L



## LAVA OUTBOARD 4T

High performance, four-stroke engine oil for use in outboard engines. It exceeds the requirements of the strict National Marine Manufacturers' Association (NMMA) FC-W specification. It shows excellent wear and corrosion protection, it resists foam formation and shearing, meeting the shear HTHS requirements of NMMA. It is recommended for gasoline-fuelled, four-stroke outboard and watercraft motors of major global OEM, such as Honda, Mercury, Yamaha, Johnson/Evinrude, Suzuki, Nissan, Tohatsu. It can be used wherever a SAE 10W-40, 15W-40, 25W-40 or straight SAE 40 oil is sought.

NMMA FC-W

CODE	GRADE/SAE	PACKAGING
JL01508	10W-40	4 x 4L



## LAVA OUTBOARD 2T

Premium quality, ashless two-stroke engine oil for use in water-cooled outboard engines. It exceeds the requirements of the strict National Marine Manufacturers' Association (NMMA) TCW-III specification and the performance requests of major manufacturers such as Evinrude, Johnson, Yamaha, Tohatsu and Mariner Mercury. It shows outstanding detergency and excellent rust protection during extended engine storage periods. It is suitable for all leading outboard engines, including the latest high horsepower units with direct fuel injection (DFI) models used in boats, snowmobiles and motorcycles, with a "premix" or injection oil system and in fuel/oil ratios from 11:1 to 100:1. It is dyed green for easy identification in the fuel.

NMMA TC-W3

CODE	GRADE/SAE	PACKAGING
JL00504	—	20L (PAIL)
JL00508	—	4 X 4L
JL00509	—	12 X 1L



## LAVA TIMBER CHAIN 30 (ISO 100)

TIMBER CHAIN is developed for the lubrication of chains and guide bars of chainsaws. It protects from corrosion, wear and rust formation, it utilises a special "tackiness" agent that prevents leaking, sticking or chattering. Its good low temperature flow properties and basestock low/high temperatures stability make it ideal for dust and dirt generating applications, and for both the summer and winter seasons.

CODE	GRADE/SAE	PACKAGING
JL05000	—	1000L
JL05001	—	208L
JL05007	—	4 x 5 L
JL05009	30 (ISO 100)	12 x 1L



CERTIFIED  
CYCLON QUALITY



**LAVA**



**GEAR**

 **DRIVELINE  
LUBRICANTS**

Driveline systems are required to handle different and increasingly heavier loads, use different materials and, overall, they operate under very different conditions. Cyclon GEAR series of driveline oils have been specifically designed to minimize wear and to handle loads and low/high temperatures, while retaining their viscometrics and ensuring that no power losses occur in the system. LPC's Cyclon GEAR oils meet the challenges and different requirements of the world's leading axle, gear and automatic transmission manufacturers, so that to ensure that your driveline system gets the maximum protection possible, while it operates as it is designed to. At the same time, you know you get the right oil and you enjoy your peace of mind.

**GEAR oils - manufactured in the EU - stand for ultimate driveline protection and reliability and your peace of mind.**









## GEAR SYN G XL

GEAR SYN G XL is a long life, low viscosity fluid, designed for use in all ZF manual and automated manual commercial transmissions. Based on a premium synthetic base-stock and a very advanced anti-wear, EP additive system, it provides for excellent low temperature fluidity giving improved protection and smooth gearshifts at low temperatures. Due to its excellent thermal and oxidative stability, it extends the life of transmission and lubricant extending drain intervals, as well as reducing service needs. It is characterised by its broad synchroniser compatibility. It is specially formulated for use in heavily loaded manual and automated manual synchronized transmissions running under very severe conditions (in terms of load, speed or temperature variations). It is, also, suitable for use in differentials (in the absence of a torque hypoid). A particularly well-suited fluid for the purpose of meeting ZF's extended drain intervals, with/without ZF-Intarder/retarder and for global OEMs (such as Renault Trucks, DAF, MAN, Iveco, etc.).

**API GL-4; MAN 341 Type E-3, 341 Type Z-4; Volvo 97305; ZF TE-ML 01L, 02L, 08, 13, 16K Meets: Eaton Europe (300.000 km/3 years), DAF, IVECO, Renault Trucks (B0032/2 Annex 3)**

CODE	GRADE/SAE	PACKAGING
JE00504	75W-80	20L (PAIL)
JE00508	75W-80	4 x 4L
JE00509	75W-80	12 x 1L



## GEAR SYN G HZ

Extreme performance multi-vehicle gear oil, suitable for gearboxes and transaxles where the manufacturer specifies a GL-4 SAE 75W-80 oil. It provides outstanding protection and lubrication of the gearbox synchronisers on all key material type, operating over a wide temperature range. It meets the requirements of most European and Asian passenger car manufacturers.

**API GL-4; BMW MTF LT-4; MB 235.10; Peugeot-Citroën PSA B71 2330; FIAT 9.55550-MZ1; Special Gear Oil MTF 94; VW G 052 178, G 060 726, G 009 317, G 052 512 Suitable: Ford WSS-M2C200-D2; GM 1940768, GM 1940182, GM 1940764; Nissan MT-XZ, MT-XZ TL (JR Type); Special Honda MTF, MTF-II; Tranself NFJ, NFP, NRJ, TRT, TRZ; Volvo 97308, 97309 Meets (always check vehicle manual): Alfa Romeo, Magma PT (Getrag), Hyundai, KIA, Land Rover, Lexus, Nissan, Opel, Renault, Saab, Toyota**

CODE	GRADE/SAE	PACKAGING
JE01004	75W-80	20L (PAIL)
JE01008	75W-80	4 x 4L
JE01009	75W-80	12 x 1L



## GEAR SYN TDL

Long life transmission and axle oil designed to provide ultimate protection to the latest heavy duty manual transmissions and axles. Produced by 100% synthetic base oils and a unique technology additive system, it provides advanced protection against wear, viscosity retention, improved fuel economy and longer service life due to its excellent thermal stability. It is an extreme performance total driveline lubricant specially formulated for use in heavily-loaded axles and synchronised transmissions of all major Japanese and European passenger cars, commercial vehicles, buses, delivery trucks, tractors and construction equipment.

**API GL-5, GL-4, MT-1; MB 235.8; Volvo 97312; Detroit Diesel DFS 93K219.01; MAN 341 Type Z2, 342 Type S1; Mack GO-J; Scania STO:1, STO 2:0A FS; Eaton Europe (transmissions); Meritor 076-N; ZF TE-ML 02B, TE-ML 05A, TE-ML 07A, TE-ML 08, TE-ML 12L, TE-ML 12N, TE-ML 16F, TE-ML 17B, TE-ML 19C, TE-ML 21A; MIL-PRF-2105E; SAE J2360**

CODE	GRADE/SAE	PACKAGING
JE01501	75W-90	208L
JE01504	75W-90	20L (PAIL)
JE01508	75W-90	4 x 4L
JE01509	75W-90	12 x 1L



## GEAR SYN EP

High performance, synthetic gear oil for transmission systems and differentials. It is manufactured with the use of advanced technology base oils and additives in order to ensure good rheological behavior in low temperatures and retention of its viscosity at high temperatures. It is suitable for hypoid gears, drive axles and final drives operating in a broad temperature spectrum, and for trucks, construction equipment, as well as passenger cars. It can, also, be used in cars' gear boxes if API GL-5 specification is sought.

**API GL-5; MIL-L-2105D; ZF TE-ML 05A, TE-ML 07A, TE-ML 12E, TE-ML 16B, TE-ML 17B**

CODE	GRADE/SAE	PACKAGING
JE02001	75W-90	208L
JE02004	75W-90	20L (PAIL)
JE02009	75W-90	12 x 1L





CERTIFIED  
CYCLON QUALITY



## GEAR EP/GL-5

High performance multigrade gear oils. They offer exceptional resistance to oxidation and corrosion and maximize performance under adverse loading and temperature conditions. Capable of improving fuel economy, they are suitable for hypoid gear, drive axles and final drives operating under high speed/shock loads in trucks, construction equipment and passenger cars. Suitable for gear boxes where a API GL-5 gear oil specification is recommended.

### 80W-90

API GL-5; MIL-L-2105D; SDFG OP-1705; MAN 342 Type M1, 342 Type M2, 342 N; ZF TE-ML 05A/TE-ML 12E/TE-ML 16B/TE-ML 17B/TE-ML 19B/TE-ML 21A (approved), TE-ML 07A, TE-ML 08, TE-ML 16C, TE-ML 16D

Suitable: Volvo 97310 (1273.10)

### 85W-90/85W-140

API GL-5; MIL L-2105D; MAN 342 Type M1, 342 Type M2; ZF TE-ML 05A, TE-ML 07A, TE-ML 08, TE-ML 12E, TE-ML 16B, TE-ML 16C, TE-ML 16D, TE-ML 21A

Suitable: Volvo 97310 (1273.10)

CODE	GRADE/SAE	PACKAGING
JE02500	80W-90	1000L
JE02501	80W-90	208L
JE02504	80W-90	20L (PAIL)
JE02508	80W-90	4 x 4L
JE02509	80W-90	12 x 1L
E03001	85W-90	208L
E03004	85W-90	20L (PAIL)
JE03501	85W-140	208L
JE03504	85W-140	20L (PAIL)



## GEAR HD/GL-4

High quality gear oil with specially selected additives for mild extreme pressure conditions. They impart good antiwear, anti-rust characteristics and oxidation stability. Recommended for the lubrication of manual gearboxes of passenger cars and commercial vehicles operating under high speed/low torque and low speed/high torque conditions. Suitable for gearboxes fitted with synchromesh.

API GL-4; MIL-L-2105; MAN 341; ZF TE-ML 02A, TE-ML 08A, TE-ML 17A

CODE	GRADE/SAE	PACKAGING
JE03701	80W	208L
JE03704	80W	20L (PAIL)
JE04001	90	208L
JE04004	90	20L (PAIL)
JE04006	90	10L (PAIL)
JE04009	90	12 x 1L
JE04200	140	1000L
JE04201	140	208L
JE04204	140	20L (PAIL)
JE04301	250	208L
JE04304	250	20L (PAIL)
JE04309	250	12 x 1L
JE04500	80W-90	1000L
JE04501	80W-90	208L
JE04504	80W-90	20L (PAIL)
JE04508	80W-90	4 x 4L
JE04509	80W-90	12 x 1L



## GEAR BV/P-CT

Specially designed oil for the lubrication of manual gear boxes and axles of passenger cars when the manufacturer requires an oil of this quality and grade. Particularly recommended for the lubrication of Peugeot and Citroën vehicles' gearboxes.

### API GL-5

Recommended: Peugeot-Citroën (PSA)

CODE	GRADE/SAE	PACKAGING
JE05004	75W-80	20L (PAIL)
JE05009	75W-80	12 x 1L



## GEAR LS/4x4

Extreme pressure gear oil for axles equipped with limited slip differential systems. It provides maximum protection in highly loaded gears subjected to shocks and seal and friction material compatibility. Suitable for vehicles' axles equipped with limited slip disc differential systems and for "all wheel drive", "all terrain" cars.

**API GL-5; MIL-L-2105D; ZF TE-ML 05C, TE-ML 16E, TE-ML 21C**

CODE	GRADE/SAE	PACKAGING
JE06501	90 (85W-90)	208L
JE06504	90 (85W-90)	20L (PAIL)
JE06509	90 (85W-90)	12 x 1L



## GEAR PRIME

Monograde high viscosity index automotive gear lubricants. Suitable for manual gearboxes and differentials of older cars that operate under light load/low speed conditions.

**API GL-1**

CODE	GRADE/SAE	PACKAGING
JE05404	80W	20L (PAIL)
JE05408	80W	4 x 4L
JE05409	80W	12 x 1L
JE05500	90	1000L
JE05501	90	208L
JE05504	90	20L (PAIL)
JE05508	90	4 x 4L
JE05509	90	12 x 1L
JE06000	140	1000L
JE06001	140	208L
JE06004	140	20L (PAIL)
JE06008	140	4 x 4L
JE06009	140	12 x 1L



## ATF S-1A

A high performance, fully synthetic, multi-vehicle automatic transmission fluid specifically formulated for Japanese passenger and light commercial vehicles. It offers excellent anti-shudder durability, which improves driver comfort and enables smoother shifting. The film thickness and antiwear performance is maintained, helping to reduce the cost of maintenance and extending the transmission lifetime. It is suitable for most European and Asian passenger cars, commercial vehicles and off-highway/construction equipment where automatic transmissions and power steering are required. It can be, also, used as a hydraulic oil in older vehicles.

**GM Dexron IIIH, Dexron IIIG, Dexron IID; Allison TES 295, TES 389, C-4; Ford Mercon®V; JASO 1-A; MAN 339 Type V1, 339 Type V2, 339 Type Z1, 339 Type Z2, 339 Type Z11; MB 236.1, MB 236.2, MB 236.3, MB 236.5, MB 236.6, MB 236.7, MB 236.9, MB 236.10, MB 236.11, MB 236.12, MB 236.14, MB 236.15, MB 236.41, MB 236.81; VOITH H55.6335, H55.6336; Volvo 97340, 97341; ZF TE-ML 03D, TE-ML 04D, TE-ML 05L, TE-ML 09, TE-ML 11A, TE-ML 11B, TE-ML 14A, TE-ML 14B, TE-ML 16L, TE-ML 20B; Honda/Acura ATF-Z1 (not CVT); DW-1; Hyundai/KIA SP-II, SP-III, JWS 3314, JWS 3317, Red-1, SP-IV, SPH-IV, SP-IV-RR; Hyundai NWS-9638; Toyota T, T-II, T-III, T-IV, WS (JWS 3324); Nissan 402, Matic-D, Matic-J, Matic-K; Mitsubishi SP-II, SP-III, Diaqueen ATF J3, ATF J2; MOPAR AS68RC; Idemitsu K17 (JATCO), JWS 3309, JWS 3324 (Aisin Warner); Mazda ATF-M III, ATF-MV, FZ; Subaru ATF, ATF-HP; Suzuki 3314, 3317; VW G 052 162, G 052 990, G 055 025, G 055 540, G 055 005, G 055 162; Audi G 052 162, G 052 990, G 055 025, G 055 005, G 055 162; BMW 3 Series 7045E, BMW 5 Series LA 2634, LT 71141, 83 22 0 142 516; PSA AL-4; NAG 1/Shell 3403; Renault DP-0; Volvo 4-/6-Speed**

CODE	GRADE/SAE	PACKAGING
JE08001	—	208L
JE08009	—	12 x 1L



CERTIFIED  
CYCLON QUALITY



## ATF PROTECT 8HP

Fully synthetic, high-performance, long-life ATF, specifically formulated for various Audi, BMW, Jaguar, Land Rover, etc. models that are fitted with ZF's 8HP-series eight-speed automatic transmission. It can, also, be used in certain ZF six-speed 6HP automatic transmissions, ensuring increased driving comfort through smoother gear shifts while at the same time reducing fuel consumption. Check the vehicle manual or/and for suitable OEM P/Ns.

**ZF TE ML-11; GM Dexron VI; Ford Mercon LV; JASO 1A-LV; Aisin AW-1, JWS 3324; Toyota WS; FIAT 9.55550-AVS; Land Rover TYK 500050, LR023288; Jaguar 02JDE26444; Honda ATF 3.1, ATF DW-1; Hyundai SP-IV; Nissan AT-Matic S Fluid**  
**Suitable: ZF LifeguardFlud 8 (P/N S671 090 312); BMW P/N 83 22 0 142 516, P/N 83 22 0 152 426, P/N 83 22 2 305 396, P/N 83 22 2 305 397, P/N 83 22 2 289 720, P/N 83 22 2 355 599; VW P/N G 055 005, P/N G 055 540, P/N G 060 162**

CODE	GRADE/SAE	PACKAGING
JE10008	—	4 X 4L
JE10009	—	12 X 1L



## ATF PROTECT NG 7-9

Fully synthetic, fuel-efficient, low viscosity ATF, specially formulated to ensure ultimate protection and superior lubrication of automatic gearboxes over extremes of operating temperatures. It is specifically formulated for vehicles fitted with Mercedes Benz' 3rd generation, nine-speed (9-G Tronic) automatic transmission (NAG3). It is also suitable for MB's seven-speed NAG2FE+ transmissions. Check the vehicle manual or/and for suitable OEM P/Ns.

**MB 236.17 (P/N A 002 989 06 03), MB 236.16 (P/N A 001 989 92 03), MB 236.15 (P/N A 001 989 77 03, P/N A 001 989 78 03)**  
**Suitable: MB NAG3, NAG2FE+, MB 9-G Tronic, 7-G Tronic+, MB 725.0xx, 722.9xx, 724.2xx**

CODE	GRADE/SAE	PACKAGING
JE10508	—	4 X 4L
JE10509	—	12 X 1L



## ATF S-DCT

Fully synthetic, multi-vehicle dual clutch transmission fluid (DCTF). It provides superior shear stability, increased friction durability and wear protection of gears and bearings. Its stable friction system ensures good shift quality over the life of the transmission giving a longer-lasting smooth shift feel to the driver, longer fluid life and extended drain intervals. It is suitable for use in passenger cars and vans with a wet dual clutch transmission. It meets the requirements of the major manufacturers: VW Group, Ford/Getrag, Volvo, Chrysler, Peugeot, Citroën and Mitsubishi.

**Volkswagen Group (VW, Audi, SEAT & Skoda) [MY >2003], Ford, Magma PT (Getrag), Volvo, FIAT-Chrysler (FCA), Peugeot-Citroën (PSA), Mitsubishi [MY >2007] w/ 6-Speed Wet-Type DCT**

CODE	GRADE/SAE	PACKAGING
JE07009	—	12 x 1L



## ATF CVT NS-2/-1

ATF CVT NS-2/-1 is a very carefully designed synthetic oil for most CVT gearboxes. It meets Nissan's NS-2 & NS-1 specifications. It offers outstanding anti-wear protection, stable friction characteristics and improved anti-shudder durability. It is suitable for continuously variable transmissions, using steel push belts or chains of a wide range of CVT-equipped passenger vehicles. It is not recommended for Hybrid E-CVT and Toroidal CVTs.

**Volkswagen Group TL 52180, G 052 180, G 052 516; Dodge/Jeep NS-2, CVTF+4; Ford CVT23, CVT30, Mercon C; GM/Saturn DEX-CVT; Honda HMMF, HCF-2; Hyundai/KIA SP-CVT 1; Mini Cooper EZL 799A; Mitsubishi CVTF-J1; Nissan NS-1, NS-2; Punch EZL 799A; Subaru Lineartronic CVTF; Suzuki TC, NS-2, CVT Green 1; Toyota TC**  
**Meets: MB 236.20, Shell Green 1V**

CODE	GRADE/SAE	PACKAGING
JE07509	—	12 x 1L





## ATF TYPE D

High quality automatic transmission gear oil in accordance with General Motors' specification Dexron III. It enables effective and smooth power transmission due to viscosity stability and the special friction characteristics it employs. It can be used under high temperature and/or load conditions. Suitable for use in automatic/manual transmissions, clutches and steering systems in various machinery, passenger cars, trucks, construction equipment etc., in accordance to the manufacturer's recommendations.

**GM Dexron III G, Dexron IID; Allison C-4; Ford Mercon®; MB 236.1, MB 236.5, MB 236.6, MB 236.7, MB 236.9; VOITH 55.6335; ZF TE-ML 02F, TE-ML 03D, TE-ML 04D, TE-ML 14A, TE-ML 17C; Caterpillar TO-2; MAN 339 Type Z-1, 339 Type Z-2, 339 Type V-1, 339 Type V-2**

**Suitable: Volvo 97340, 97341**

CODE	GRADE/SAE	PACKAGING
JE09000	—	1000L
JE09001	—	208L
JE09004	—	20L (PAIL)
JE09008	—	4 x 4L
JE09009	—	12 x 1L



## ATF TYPE A

Especially formulated lubricant for automatic transmissions meeting General Motors' TASA (Type A Suffix A) level requirements. Suitable for automatic and semi-automatic transmissions and other cases, according to the manufacturer's recommendations.

**GM TASA; Allison C-3; MB 236.2; Caterpillar TO-2**

CODE	GRADE/SAE	PACKAGING
JE08501	—	208L
JE08504	—	20L (PAIL)
JE08508	—	4 x 4L
JE08509	—	12 x 1L



CERTIFIED  
CYCLON QUALITY



**ATF**

## SPECIAL PRODUCTS

### AUTOMOTIVE SPECIAL PRODUCTS

The overall protection of the vehicle and the prolongation of its engine's life being of paramount importance, Cyclon series of complementary, special automotive products will make sure just that; our high quality coolants, power steering and suspension fluids, brake fluids and, windscreen cleaners are intended to offer longer engine life and to protect your vehicle.

**Cyclon SPECIAL automotive fluids -  
manufactured in the EU - stand for superior  
engine and vehicle protection.**









## ADBLUE

High cleanliness, ready-to-use diesel exhaust fluid (DEF) of 32.5% urea in ultra pure water (AUS32). It is used as an additive in heavy duty truck and bus diesel engines that are equipped with selective catalytic reduction systems with the objective to reduce the engine nitrogen oxides (NOx). It is suitable for Euro IV, V and Euro VI engines. NOT to be added in the fuel tank. It is stored in steel tanks next to the fuel tank and is sprayed directly into the exhaust gases pipe. Its consumption is, typically, between 2-7% (depending on the Euro standard to be covered) of the fuel consumption.

**ISO 22241-1: 2019; AUS 32 Part 1/2; DIN 70070; CEFIC**

CODE	GRADE/SAE	PACKAGING
CAB0110	—	10L (PAIL)
CAB0120	—	20L (PAIL)



## RADIATOR

Concentrated antifreeze coolant, providing protection against the cold of winter and the heat of summer depending on its dilution in de-ionized water. It contains mono-ethylene glycol and corrosion inhibitors and provides excellent aluminum corrosion protection and heat transfer properties. It is suitable for both diesel and gasoline-powered, liquid-cooled engines and other closed water circuits operating under extreme temperature conditions.

**AFNOR NF R15-601; SAE J1034; ASTM D3306, D4656, D4985; BS 6580:2010; AS 2108; CUNA NC 956-16; ONORM V 5123; UNE 26361-88; FFV Heft R443; NATO S-759; Meets: VW Group TL-774C (G11); MB 325.0, MB/DBL 7700.20; MAN 324 NF**

CODE	GRADE/SAE	PACKAGING
CC01001	—	208L
CC01004	—	20L (PAIL)
CC01008	—	4 x 4L
CC01009	—	12 x 1L



## RADIATOR LL (G12+)

A nitrite-, amine-, phosphate-, silicate- and borate-free coolant based on ethylene glycol. It contains OAT corrosion inhibitors that effectively protect the vital parts of the cooling system against corrosion and deposits for a very long time. It must be diluted with water before use. It exceeds the requirements of all major car manufacturers. Mixed with water, it provides for outstanding protection against frost, corrosion and heating in all modern vehicles, especially those with aluminium engines. It provides effective protection for long periods. Suitable for heavy trucks (650,000km) and passenger cars (250,000km). A 50% dilution provides frost protection down to -40°C.

**BS 6580:2010; AFNOR NF R15-601:2020; ASTM D3306, D4656, D4985, D6210 Type III-FF; SAE J1034; SDFG EC-1599A; CUNA NC 956-16; NATO S-759; JIS K2234; AS 2108; FVV Heft R443; UNE 26361-88 Meets: VW Group TL-774D (G12), TL-774F (G12+); MB 325.3; MAN 324 Type SNF; MTU MTL 5048; GM 6277M; Ford WSS-M97-B44D; Volvo 1286083, VCS (STD 418-0001); Renault 41-01-001; DAF 74002; Scania TI 02-98 0813 T/B/M sv.**

CODE	GRADE/SAE	PACKAGING
CC01501	—	208L
CC01504	—	20L (PAIL)
CC01508	—	4 x 4L
CC01509	—	12 x 1L
CC06000	—	1000L



## RADIATOR LL G13

G13 coolant is a new technology, very long life undiluted coolant based on organic inhibitors in combination with mineral inhibitors (silicate), high purity MEG and Glycerin. Hence it delivers not only maintenance-free protection against freezing and boiling but also long-lasting protection against corrosion. It is suitable for the protection of all modern aluminum circuits of professional and passenger vehicles. It can be mixed with all coolants meeting the G12++ (VW TL 774 G) specification. Replace every 3 to 5 years.

**BS 6580; ASTM D3306; VW Group TL-774J (G13) P/N: VW G 013 A8J 1G, G 013 A8J M1; MB 000 989 28 25, MB 000 989 28 25 11; Porsche 000 043 301 47 Compatible: G12++, G12+, G12, G11**

CODE	GRADE/SAE	PACKAGING
CC02004	—	20L (PAIL)
CC02009	—	12 x 1L





CERTIFIED  
CYCLON QUALITY



## CYCLONFLU LL (G12+)

Ready-to-use, long life antifreeze, recommended for all cooling circuits in modern aluminium or cast iron engines in passenger cars, vans, heavy trucks and construction equipment. It provides freezing protection down to -40°C.

**BS 6580:2010; AFNOR NF R15-601:2020; ASTM D3306, D4656, D4985, D6210 Type III-FF; SAE J1034; SDFG EC-1599 A; CUNA NC 956-16; NATO S-759; JIS K2234; AS 2108; FVV Heft R443; UNE 26361-88**  
Meets: VW Group TL-774D (G12), TL-774F (G12+); MB 325.3, MB 326.3; MAN 324 Type SNF; MTU MTL 5048; GM 6277M; Ford WSS-M97-B44D; Volvo 1286083, VCS (STD 418-0001); Renault 41-01-001; DAF 74002; Scania TI 02-98 0813 T/B/M sv.

CODE	GRADE/SAE	PACKAGING
CC02501	—	208L
CC02504	—	20L
CC02508	—	4 x 4L
CC02509	—	12 x 1L



## CYCLONFLU LL G13

CYCLONFLU LL G13 coolant is a new technology, very long life ready-to-use coolant, based G13 and deionized water. It is suitable for the protection of all modern aluminium circuits of professional and passenger vehicles. It can be mixed with all coolants meeting the G12++ (VW TL 774 G) specification.

**BS 6580; ASTM D3306; VW Group TL-774J (G13)**  
P/N: VW G 013 A8J 1G, G 013 A8J M1; MB 000 989 28 25, MB 000 989 28 25 11; Porsche 000 043 301 47  
Compatible: G12++, G12+, G12, G11

CODE	GRADE/SAE	PACKAGING
CC03008	—	4 x 4L



## CYCLONFLU PLUS

Ready-to-use solutions of Radiator in deionized water. It provides frost protection down to -21 °C. It is suitable for all radiators, including modern aluminium ones, in both diesel and gasoline-powered vehicles.

**AFNOR NF R15-601; SAE J1034; ASTM D3306, D4656, D4985; BS 6580:2010; AS 2108; CUNA NC 956-16; ONORM V 5123; UNE 26361-88; FVV Heft R443; NATO S-759;**  
Meets: VW Group TL-774-C (G11); MB 325.0, MB 326.0, MB/DBL 7700.20; MAN 324 NF

CODE	GRADE/SAE	PACKAGING
CC03501	—	208L
CC03504	—	20L (PAIL)
CC03508	—	4 x 4L
CC03509	—	12 x 1L



## CYCLONFLU

Ready-to-use solutions of Radiator in deionized water. It provides frost protection down to -15°C. It is suitable for all radiators, including modern aluminium ones, in both diesel and gasoline-powered vehicles.

**AFNOR NF R15-601; SAE J1034; ASTM D3306, D4656, D4985; BS 6580:2010; AS 2108; CUNA NC 956-16; ONORM V 5123; UNE 26361-88; FVV Heft R443; NATO S-759**  
Meets: VW Group TL-774C (G11); MB 325.0, MB 326.0, MB/DBL 7700.20; MAN 324 NF

CODE	GRADE/SAE	PACKAGING
CC04000	—	1000L
CC04008	—	4 x 4L
CC04009	—	12 x 1L



## FLUSHING OIL

Special solvent-free, detergent/dispersant formula fluid, designed to clean engines (with/without aftertreatment systems) - as well as manual gearboxes and differentials - prior to oil change.

CODE	GRADE/SAE	PACKAGING
J113001	—	208L
J113008	—	4 x 4L





## DISTILLED WATER

It is especially treated in ion exchange columns to remove the salts and chlorine contents. Ideal for topping up car batteries, radiators and screen washers.

CODE	GRADE/SAE	PACKAGING
M000438	—	4 x 4L



## L.H.M. FLUID

Special fluid manufactured for use in central hydraulic systems of Citroen and Peugeot cars. To be used only in hydraulic reservoirs painted green. Not to be used in hydraulic reservoirs painted black, where synthetic LHS fluids or vegetable oils are used. It is not compatible with DOT brake fluids. It is suitable for the brakes, power steering, suspension and shock absorbers of the PSA Group (Peugeot and Renault) cars.

**ISO 7308; DIN 51524 Part 3 HVLP; Peugeot-Citroën PSA B71.2710; FIAT 9.55597; IVECO 18-1823**

CODE	GRADE/SAE	PACKAGING
M000897	—	12 x 1L



## BRAKE FLUID 4

Synthetic fluid with special additives designed to optimise the operation of the brake system. DOT 4 is especially formulated to offer increased safety against water contamination that can result in a lower operational efficiency of the brake system. It is suitable for every brake system, which utilises synthetic brake fluids and requires DOT 4. It should not be mixed with either brake fluids based on mineral oils or DOT 5 brake fluids.

**SAE J1704, J1703; FMVSS No. 116 (§571.116) DOT 4 /3; ISO 4925 Class 4/3; JIS K2233; CUNA NC 956-01; INTA UNE 26-109-88**  
**Meets: FIAT 9.55597 (Contr. Tech. Ref. No F005.F15); MOPAR MS-90039 (MS-9971)**

CODE	GRADE/SAE	PACKAGING
M001118	—	48 x 250ML



## BATTERY FLUID

It is especially treated in ion exchange columns to remove the salts and chlorine contents. Suitable for filling up car batteries.

CODE	GRADE/SAE	PACKAGING
M000517	—	48 x 500ML



## CLEAN GLASS WINTER

Special windscreen cleaning fluid containing cleaning agents diluted in de-ionized water and ethyl alcohol, and in different dilution ratios that vary with ambient temperatures.

CODE	GRADE/SAE	PACKAGING
C040718	—	24 x 300ML



## CLEAN GLASS SUMMER

Special windscreen cleaning fluid containing cleaning agents diluted in de-ionized water.

CODE	GRADE/SAE	PACKAGING
C040818	—	24 x 300ML



CERTIFIED  
CYCLON QUALITY



**SPECIAL  
PRODUCTS**

**INDUSTRIAL**

 **INDUSTRIAL  
LUBRICANTS**

Cyclon INDUSTRIAL series of lubricants surpass the very different requirements of all core industrial segments systems due to our 35 years of hands-on experience developing superior technology lubricants. Our comprehensive product range is engineered to meet high levels of performance in a variety of industrial applications (from hydraulics and compressors to pneumatic tools and greases, for example), to ensure minimal operational or maintenance costs and avoid undesirable breakdowns.

**INDUSTRIAL oils – manufactured in the EU – stand for superior performance and overall equipment reliability for your peace of mind.**









## TITANUS EP SYNPAO

Premium tier, fully synthetic industrial gear oils formulated to deliver a high level of microscopic wear resistance and bearing protection. They are formulated with a specially selected PAO-based basestock and a top of the class additive system that will provide outstanding thermal stability and high load-carrying capacity. Compatible with the elastomers and paints found in modern gearbox designs.

**DIN 51517 Part 3 CLP (2008/11), DIN 51502; ISO 6743-6 (ISO-L-CKC/ISO-L-CKD), ISO 12925-1 CKC, CKD (2002); US Steel 224 (Updated); David Brown S1.53.101; AGMA 9005-E02 (2002)**

**Meets: Flender AG, Milacron EP GO**

CODE	GRADE/ISO	PACKAGING
J104504	220	20L (PAIL)
J105001	320	208L
J105004	320	20L (PAIL)



## TITANUS EP

High quality, heavy duty, lead-free gear lubricants with extreme pressure (EP) additives. A specially balanced additive system provides extreme pressure and anti-wear protection, rust and corrosion prevention, increased oxidation stability and resistance to foaming. It also provides excellent load-carrying capacity. They are recommended for all types of enclosed gear drives. They are suitable for both circulation and splash lubrication systems and are particularly recommended for gear sets operating under heavy or shock loads.

**US Steel 224; David Brown S1.53.101; ISO 6743-6 (ISO-L-CKB, ISO-L-CKC, ISO-L-CKD, ISO-L-CKG); DIN 51517 Part 3 CLP (2008/11), DIN 51502; AGMA 9005-E02**

CODE	GRADE/ISO	PACKAGING
J100501	68	208L
J100504	68	20L (PAIL)
J101001	100	208L
J101004	100	20L (PAIL)
J101501	150	208L
J101504	150	20L (PAIL)
J102000	220	1000L
J102001	220	208L
J102004	220	20L (PAIL)
J102501	320	208L
J102504	320	20L (PAIL)
J103001	460	208L
J103004	460	20L (PAIL)
J103501	680	208L
J103504	680	20L (PAIL)
J104001	1000	208L



## CYBIO-GEAR

High performance, synthetic biodegradable lubricants for enclosed industrial gears and bearings in environmentally sensitive applications.

**ISO 15380 (HEES); DIN 51517 Part 3 CLP (2008/11), DIN 51502**  
**Meets: US Steel 224; AGMA 9005-E02; EU Ecolabel criteria**

CODE	GRADE/ISO	PACKAGING
J105501	220	208L
J105504	220	20L (PAIL)
J106001	320	208L
J106004	320	20L (PAIL)



CERTIFIED  
CYCLON QUALITY



## HYDRAULIC SP

Premium quality, high viscosity index, anti-wear hydraulic oils designed to meet the all-season requirements of major hydraulic system manufacturers and users. The high VI and low pour points ensure pump start-up at low temperatures while maintaining oil viscosity at high operating temperatures. The viscosity retention provides effective anti-wear protection to pumps even in severe service hydraulic applications of high pressure and wide temperature variations.

**DIN 51524 Part 3 HVLP; ISO 6743-4 (ISO-L-HV), ISO 11158 HV; Denison (Parker) HF-0, HF-2; AFNOR NF E48-603 HV, NF E48-690 (dry), NF E48-691 (wet); Vickers M-2950-S, I-286-S; Cincinnati Machine P68 (ISO 32), P69 (ISO 68), P70 (ISO 46); Case IH Poclairn**

CODE	GRADE/ISO	PACKAGING
J118001	15	208L
J118004	15	20L (PAIL)
J118500	32	1000L
J118501	32	208L
J118504	32	20L (PAIL)
J119000	46	1000L
J119001	46	208L
J119004	46	20L (PAIL)
J119500	68	1000L
J119501	68	208L
J119504	68	20L (PAIL)
J120001	100	208L
J120004	100	20L (PAIL)



## HYDRAULIC

High quality oils with extreme pressure (EP) additives for hydraulic systems. They provide outstanding protection against wear, corrosion and oxidation. The careful use of additives ensures quick air release without excessive foaming, good chemical stability in the presence of moisture and superior filterability.

**DIN 51524 Part 2 HLP; Denison (Parker) HF-0, HF-2, HF-1; AFNOR NF E48-603 HM; Vickers M-2950-S, I-286-S; Eaton 35VQ25; Cincinnati Machine P48 (ISO 32), P69 (ISO 68), P70 (ISO 46); ISO 11158 HM (CETOP RP 91 H), ISO 6743-4 (ISO-L-HM); Bosch Rexroth RE 90220; SAE MS 1004 (HM); JCMAS P041 HK; AGMA 9005-E02 RO; GM LS-2; US Steel 126, 127; SEB 181222**

CODE	GRADE/ISO	PACKAGING
J115401	22	208L
J115404	22	20L (PAIL)
J115500	32	1000L
J115501	32	208L
J115504	32	20L (PAIL)
J116000	46	1000L
J116001	46	208L
J116002	46	60L
J116004	46	20L (PAIL)
J116006	46	10L (PAIL)
J116008	46	4 x 4L
J116013	46	208L
J116016	46	18L (PAIL)
J116500	68	1000L
J116501	68	208L
J116504	68	20L (PAIL)
J116508	68	4 x 4L
J117000	100	1000L
J117001	100	208L
J117004	100	20L (PAIL)
J117500	150	1000L
J117501	150	208L
J117504	150	20L (PAIL)





## HYDRAULIC ZF

Very high purity, zinc-free hydraulic oils with excellent demulsification properties, resistance to ageing, corrosion protection and anti-wear properties.

**Denison (Parker) HF-0, HF-1, HF-2; ISO 6743-4 (ISO-L-HM); DIN 51524 Part 2 HLP; AF-NOR NF E48-603 HM; SS 155434; VDMA 24318; SEB 181222; US Steel 127, 136**

CODE	GRADE/ISO	PACKAGING
JI20501	32	208L
JI20504	32	20L (PAIL)
JI21001	46	208L
JI21004	46	20L (PAIL)
JI21501	68	208L
JI21504	68	20L (PAIL)



## HYDROPREMIUM

Enhanced quality hydraulic lubricants boosted with a balanced anti-wear, EP and anti-corrosion additive chemistry. Suitable for the lubrication of circulation and hydraulic systems.

**DIN 51524 Part 2 HLP, DIN 51502 Cat. HLP; ISO 6743-4 (ISO-L-HM); AFNOR NF E48-603 HM**

CODE	GRADE/ISO	PACKAGING
JI13501	32	208L
JI13504	32	20L (PAIL)
JI14000	46	1000L
JI14001	46	208L
JI14004	46	20L (PAIL)
JI14006	46	10L (PAIL)
JI14500	68	1000L
JI14501	68	208L
JI14504	68	20L
JI14506	68	10L
JI15001	100	208L
JI15004	100	20L (PAIL)



## HYDRAULIC HLP-D

High performance hydraulic fluid containing a highly specialized zinc-free (ashless) and detergent/dispersant additive system. It is particularly recommended for use in hydraulic systems of machine tools in demanding industrial applications where water-mixed cutting fluids may enter the hydraulic system, as well as shore/offshore applications that experience high ingress of water or contamination e.g., mobile hydraulic units (excavators, bulldozers, wheel loaders, truck hydraulic systems).

**DIN 51524 Part 2 HLP (excl. demulsifying properties); Daimler DBL 6721-1; ISO 6743-4 (ISO-L-HLPD); ISO 11158 (HM)**

CODE	GRADE/ISO	PACKAGING
JI21800	46	1000L



## CYBIO-HFE

Fully synthetic, zinc-free, rapidly biodegradable, high-performance hydraulic fluid. It is suitable for hydraulic systems in environmentally sensitive shore/offshore applications.

**ISO 15380 (HEES)  
Meets: US EPA VGP (2013); EU Ecolabel criteria; Swedish Standard 155434; Sperry Marine; Rolls Royce Marine**

CODE	GRADE/ISO	PACKAGING
JI22001	46	208L
JI22004	46	20L (PAIL)
JI22501	68	208L
JI22504	68	20L (PAIL)



CERTIFIED  
CYCLON QUALITY



## HERCULES SYNPAO

Premium quality, fully synthetic compressor oils. They provide superb protection against deposits formation, rust and oxidation, low evaporation losses and low tendency for the build-up of residue. They offer excellent oxidation resistance and superior cleanliness over long service periods. They are suitable for screw, rotary, vane and centrifugal stationary and mobile air compressors. They can be used for single-stage as well as multi-stage compressors. They exceed the requirements of all major air compressor OEMs, such as Atlas Copco, Bauer, Ingersoll Rand, etc.

**DIN 51506 VDL; ISO 6743-3 (ISO-L-DAG, ISO-L-DAH, ISO-L-DAJ)**

CODE	GRADE/ISO	PACKAGING
J125501	46	208L
J125504	46	20L (PAIL)
J126001	68	208L
J126004	68	20L (PAIL)



## HERCULES SYNPOE

Premium quality, reciprocating air compressor lubricant based on high performance polyolesters and incorporating the latest additive technology to provide outstanding performance in the most demanding applications. Formulated for all industrial reciprocating air compressors. Specially recommended for reciprocating compressors operating at continuously high pressures and high discharge temperatures.

**DIN 51506 VDL; ISO 6743-3 (ISO-L-DAA, ISO-L-DAB, ISO-L-DAC)**

CODE	GRADE/ISO	PACKAGING
J126501	100	208L
J126504	100	20L (PAIL)



## HERCULES LPG

Synthetic polyalkylene glycol-based, compressor lubricant for use in enclosed reciprocating compressors operating in LNG / methane, ethane, LPG / propane / butane, ethylene, propylene, butadiene, ammonia, vinylchloride and dry inert gases environments.

**ISO 6743-3 (ISO-L-DAA, ISO-L-DAB, ISO-L-DAC)**  
**Meets: Linde, Burckhardt Compression**

CODE	GRADE/ISO	PACKAGING
J125001	150	208L
J125004	150	20L (PAIL)



## HERCULES

High quality compressor oils of VDL type with low evaporation losses, as defined by DIN 51506. They have very high thermal and oxidation stability resulting to low coking tendencies and excellent ageing resistance. They are fortified with zinc-free anti-wear additives ensuring excellent wear protection and very good filterability. The grades ISO 46 and 68 are particularly recommended for rotary screw and vane air compressors. The grades ISO 68 to 100 are suitable for use in any single- or multi-stage reciprocating compressors.

**DIN 51506 VDL (air exhaust 220°C); ISO 6743-3 (ISO-L-DAA, ISO-L-DAB, ISO-L-DAG, ISO-L-DAH)**

CODE	GRADE/ISO	PACKAGING
J123001	32	208L
J123501	46	208L
J123504	46	20L (PAIL)
J124001	68	208L
J124004	68	20L (PAIL)
J124009	68	12 X 1L
J124501	100	208L
J124504	100	20L (PAIL)



## TURBINE

Premium quality turbocharger oils designed to provide superior thermal and oxidative stability in severe service operations. They are formulated to provide all the performance requirements of a lubricant for use in modern steam and medium duty gas turbines. It has been designed to enable the higher oxidation performance required by modern turbine oil specifications including RPVOT and TOST requirements. They provide excellent anti-rust protection and anti-foam and water separation. Suitable for turbines in industrial and marine environments. They are, also, recommended for circulating systems requiring R&O oils, as well as in hydraulic systems requiring an R&O-type oil (low pressure).

**DIN 51515 LTD; ISO 6743-5 (ISO-L-TGA, ISO-L-TSA); AGMA R&O; B.S. 489; MIL-L-17672D; Siemens TLV 9013 04**

CODE	GRADE/ISO	PACKAGING
J128001	32	208L
J128004	32	20L (PAIL)
J128501	46	208L
J128504	46	20L (PAIL)
J129001	68	208L
J129004	68	20L (PAIL)
J129501	100	208L
J129504	100	20L (PAIL)



## LEDA

Advanced bearing and circulating oil formulated to provide outstanding service in many hydraulic applications that do not require anti-wear protection. They contain anti-rust and anti-foam agents and exhibit excellent demulsibility properties. They are appropriate for the lubrication of bearings, vacuum pumps and industrial gears where the highest thermal stability is required. Recommended for the lubrication of plain and rolling bearings as well as for lightly loaded spur, bevel, helical and worm gears.

**DIN 51524 Part 1 HL, 51517 Part 1 CL; ISO 6743-4 (ISO-L-HL), 6743-6 (ISO-L-CKB)**

CODE	GRADE/ISO	PACKAGING
J108001	100	208L
J108004	100	20L (PAIL)
J108501	150	208L
J108504	150	20L (PAIL)
J109001	220	208L
J109004	220	20L (PAIL)
J109501	320	208L
J109504	320	20L (PAIL)
J110000	460	1000L
J110001	460	208L



## ROCK DRILL

Heavy duty lubricants with extreme pressure and adhesion additives. Suitable for pneumatic and cool the mechanisms of air-operated rock drills used under high pressure/temperature conditions in quarries and construction works.

**ISO 6743-11**

CODE	GRADE/ISO	PACKAGING
J130001	46	208L
J130004	46	20L (PAIL)
J130504	68	20L (PAIL)
J131001	100	208L
J131004	100	20L (PAIL)



## AXEL

Heavy duty lubricants based on highly refined mineral oils that contain additives to enhance tackiness, anti-wear behavior and stick-slip characteristics. Specially designed for the lubrication of machine tool slides and tables. They are suitable for machine tool slideways operating under extreme pressure and high temperature conditions. ISO 68 can also be used as a hydraulic fluid in case of common lubrication systems.

**DIN 51524 Part 2 HLP; ISO 6743-13**

CODE	GRADE/ISO	PACKAGING
J133500	68	1000L
J133501	68	208L
J133504	68	20L (PAIL)
J134001	220	208L
J134004	220	20L (PAIL)
J134101	320	208L





CERTIFIED  
CYCLON QUALITY



## SUPER LIFT

Special lubricant for the hydraulic system employed in elevators. They ensure the smooth and consistent performance of the system and provide excellent air release properties. Recommended for all types of hydraulic lifts.

**DIN 51524 Part 2 HLP**

CODE	GRADE/ISO	PACKAGING
JI34501	46	208L
JI34504	46	20L (PAIL)
JI35004	68	20L (PAIL)



## HTO THERMO

Low viscosity lubricant with special anti-oxidation additives. Due to its high specific heat and heat conductivity coefficients, high heat transfer rates are possible. It is suitable for heat transfer systems operating between 10°C and 320°C. It is to be used in closed-circulated heat transfer systems in industrial applications, such as in the process industry, chemical plants, textile productions, etc. It can, also, be used for steel quenching processes.

**ISO 6743-12**

CODE	GRADE/ISO	PACKAGING
JI31500	—	1000L
JI31501	—	208L
JI31504	—	20L (PAIL)



## MATRIX

General purpose, water-miscible cutting fluid concentrate. When mixed with water, it forms a milky white emulsion. The product must be stored in a cool place. It should always be taken into consideration that the mixing is done by adding the oil in the water and not vice versa. Suitable for all general purpose machining operations of a wide variety of steel and non steel alloys where cooling is essential to the operation. The usual mixing ratio with water is 5%.

**ISO 6743-7 (ISO-L-MAA)**

CODE	GRADE/ISO	PACKAGING
JI32000	—	1000L
JI32001	—	208L
JI32004	—	20L (PAIL)



## STEELCUT

Multi-purpose, EP, neat cutting oil. It consists of a highly refined mineral oil and chlorine-free extreme pressure additives. It is suitable for a variety of operations: milling, turning, deep hole drilling of medium and high tensile steel alloys and cast iron.

**ISO 6743-7 (ISO-L-MHD)**

CODE	GRADE/ISO	PACKAGING
JI32501	—	208L
JI32504	—	20L (PAIL)



## ALUCUT

High quality, multi-purpose, neat, cutting oil. It consists of a highly refined mineral base-stock and an advanced chlorine-free, extreme pressure, "inactive sulphur" additive package. It is suitable for a variety of metalworking operations, such as gear cutting, high speed hobbing, thread grinding, milling and honing on a variety of non-ferrous (e.g. copper, bronze, etc.) and low medium tensile steel metal applications.

**ISO 6743-7 (ISO-L-MHC)**

CODE	GRADE/ISO	PACKAGING
J133001	—	208L



## METALFLUID

High viscosity index monograde lubricant. It is a special product suitable for the lubrication of metal casts.

CODE	GRADE/SAE	PACKAGING
J140000	—	1000L
J140001	—	208L
J140005	—	15L (PAIL)



## COMET

Naphthene-based refrigerating oils meeting the requirements defined by DIN 51503 type KC/KA, with very high thermal stability and very good low temperature viscosity. Suitable for the lubrication of coolant compressors (reciprocating or rotary) operating with ammonia or halogenated hydrocarbons. They can be used with all types of CFC (chlorofluorocarbon) refrigerants, such as R12, R22, R502.

**DIN 51503 KAA, 51503 KA, 51503 KC; ISO 6743-3 (ISO-L-DRA); B.S. 2626/75**  
**Meets: Bock, Howden, York, Grasson, Carrier, Sabroe**

CODE	GRADE/ISO	PACKAGING
J138001	46	208L
J138004	46	20L (PAIL)
J138504	68	20L (PAIL)



## COMET SYNPOE

High efficiency, high environmental awareness, fully synthetic refrigerating lubricant. It is produced by poly-oleo-ester base oils and a balanced additive package to ensure excellent lubricity, anti-wear protection and thermal/ chemical stability. It is ideally suitable for all new-type hydrofluorocarbon (HFC) refrigerants (R134a, R404a, R407c, R410a/b, etc.), and for domestic or industrial application environments.

**DIN 51503 KD; ISO 6743-3 (ISO-L-DRD)**  
**Meets: Bock, Howden, York, Grasson**

CODE	GRADE/ISO	PACKAGING
J139004	68	20L (PAIL)



CERTIFIED  
CYCLON QUALITY



## PREMIUM

High viscosity index lubricants fortified with anti-oxidant, anti-corrosion, anti-foaming and anti-freezing additives. They resist deposit formation and protect metal surfaces from rust and corrosion. Suitable for general machinery lubrication and low load hydraulic and circulating systems.

CODE	GRADE/SAE	PACKAGING
J111501	10W	208L
J111504	10W	20L (PAIL)
J111508	10W	4 x 4L
J111509	10W	12 x 1L
J112001	30	208L
J112004	30	20L (PAIL)
J112008	30	4 x 4L
J112009	30	12 x 1L
J112504	40	20L (PAIL)
J112508	40	4 x 4L
J112509	40	12 x 1L



## SILVER

Premium quality pure paraffinic mineral lubricants with good viscosity retention properties due to their high viscosity index. They do not contain additives. Suitable for general tool lubrication where a simple (without additives) mineral oil is adequate. It is suitable for wooden casts (special forms for concrete shaping).

CODE	GRADE/SAE	PACKAGING
J110500	10	1000L
J110501	10	208L
J110504	10W	20L (PAIL)
J110506	10W	10L (PAIL)
J110508	10W	4 x 4L
J110509	10W	12 x 1L
J111000	30	1000L
J111001	30	208L
J111004	30	20L (PAIL)
J111006	30	10L (PAIL)
J111008	30	4 x 4L
J111009	30	12 x 1L



## ELECTRO

A non-inhibited insulating oil manufactured from high quality naphthenic feedstocks. It offers good dielectric properties, good oxidation stability and provides efficient heat transfer. It has excellent low temperature properties achieved without the use of pour point depressants. It is suitable for high voltage transformers, switchgears and other electrical equipment.

CODE	GRADE/ISO	PACKAGING
J135501	—	208L
J135504	—	20L (PAIL)

**B.S. 148 Class I; IEC 296 Class I, 296 Class II, 60296 Ed. 4 (2012)**





## WHITE OIL (TECH.)

Highly refined, light viscosity, paraffinic oil of non-staining performance. Blended from highly refined mineral oils, it is used as a lubricant in textile applications, in the paper industry, as a process oil in the food industry, or any other industry where the oil must not cause a stain.

**FDA CFR 178.3620b, CFR 178.3620c**

CODE	GRADE/ISO	PACKAGING
J137501	15	208L
J137504	15	20L (PAIL)



## WHITE OIL

Pharmaceutical white oils made by high quality, extremely refined paraffinic oils. They are aromatic-free paraffinic oils complying to the very strict Pharmacopoeia purity requirements. They are suitable for use in the production of medicines, cosmetics, the food industry and other applications that require extremely clean base oils.

**FDA CFR 178.3570 (NSF H1), CFR 172.878 (NSF H3), CFR 178.3620a; InS H1/3H**  
**Meets: FUI XI; DAB 10; US Pharmacopeia XXX; NF XXV; British Pharmacopeia (BP) 2005; European Pharmacopeia (Ph. Eur.) V Ed.**

CODE	GRADE/ISO	PACKAGING
J136001	15	208L
J136004	15	20L (PAIL)
J136501	32	208L
J136504	32	20L (PAIL)
J137001	68	208L
J137004	68	20L (PAIL)



CERTIFIED  
CYCLON QUALITY



**INDUSTRIAL**



# GREASE

## GREASE

The new series of "INNOVA" and "PREMUS" greases are produced in the ultra-modern and extremely flexible production unit of LPC that was designed and manufactured in cooperation with ABB Cellier Group. The new unit can produce various types of greases, from conventional commodity types to the more advanced complex soap or/and synthetic greases, covering in full the demands of the latest quality specs/standards of all main OEM and certification bodies worldwide.

**The Cyclon line of Greases -manufactured in the European Union- provides higher performance and overall reliability of your equipment or machinery.**







**INNOVA™**



**PREMUS™**



## INNOVA™ COMPLEX/MLB

Very high performance, lithium complex-soaped grease, enhanced with antiwear/extreme pressure additives and MoS2 for very harsh (i.e. in the presence of water, dust, mud/sludge and subjected to excessive heat) applications requiring extremely high wear and friction control and water resistance. Highly recommended for heavily-loaded bearings and sliding mechanisms to be found in the steel and mining industries, in particular.

**DIN 51825 KPF2N-20; ISO 6743/9 L-X-BDHB2**

CODE	GRADE/NLGI	PACKAGING
JG08031	2	DRUM 180KG
JG08036	2	15KG (PAIL)



## INNOVA™ COMPLEX

Premium quality, highly stable, multipurpose, EP/AW - enhanced, lithium complex-soaped grease, suitable for loaded bearings, seals or mechanisms to be found in damp/wet or corrosive, high operating temperature-subjected environments. It is suitable for central lubrication systems in a wide range of heavy duty automotive, industrial or marine applications, as it provides for enhanced load-carrying capabilities and excellent wear protection.

**NLGI 1: DIN 51825 KP1N-30; ISO 6743/9 L-X-CDHB1**  
**NLGI 2: DIN 51825 KP2N-30; ISO 6743/9 L-X-CDHB2; Meets: Volvo STD 97720**

CODE	GRADE/NLGI	PACKAGING
JG07031	1	DRUM 180KG
JG07036	1	15KG (PAIL)
JG07531	2	DRUM 180KG
JG07536	2	15KG (PAIL)
JG07542	2	12 X 0,4KG



## INNOVA™ COMPLEX/WTR

Extreme performance, calcium sulphonate complex-soaped grease with EP additives and outstanding anti-rust/-corrosion properties for severe duty (i.e. shocks/loads-subjected, in the presence of water, dust, mud, high temperatures) applications. It is intended for the lubrication of bearings and sliding mechanisms in extremely demanding processes, such as continuous casting operations or rolling mills in the steel industry, wet and dry (felt rolls) sections in the paper industry and, overall, wet/damp shore/offshore environments.

**DIN 51825 KP2P-20; ISO 6743/9 L-X-BEIB2**

CODE	GRADE/NLGI	PACKAGING
JG09031	2	DRUM 180KG
JG09036	2	15KG (PAIL)



## INNOVA™ COMPLEX/WTR 1.5

Very high performance, EP-boosted calcium sulphonate complex - soaped grease with outstanding anti-rust/-corrosion properties for severe duty industrial applications (i.e. shocks/loads-subjected, in the presence of water, dust, mud, high temperatures). It is particularly recommended for central lubrication systems in highly-demanding processes, such as continuous casting operations and rolling mills in the steel industry and wet and dry (felt rolls) sections in the paper industry.

**DIN 51825 KP1/2N-20; ISO 6743/9 L-X-BDIB1/2**

CODE	GRADE/NLGI	PACKAGING
JG08531	1.5	DRUM 180KG
JG08536	1.5	15KG (PAIL)
JG08542	1.5	12 X 0,4KG



## INNOVA™ SYNCOMPLEX/TF

Premium, highly stable, synthetic grease with PTFE (Teflon®) and a top quality lithium complex soap. With a very high dropping point to ensure viscosity retention in very high operating temperatures, it is ideal for drum and high temperature disk brake wheel bearings, fifth wheels, chassis components, U-joints, kingpins, clutch bearings, ball and roller bearings and conveyors in automotive applications. Also suitable for elevated temperature industrial applications where lithium, lithium complex and extreme pressure synthetic greases would be normally specified.

**DIN 51825 KPHCF2P-25; ISO 6743/9 L-X-CEHB2**

CODE	GRADE/NLGI	PACKAGING
JG09536	2	15KG (PAIL)
JG09542	2	12 X 0,4KG





CERTIFIED  
CYCLON QUALITY



## INNOVA™ SYN/LT

Long service, EP-enhanced, lithium-thickened, synthetic grease, specifically intended for demanding low temperature applications, such as machine tool spindles, control equipment, small electric motors, robots and equipment in extremely low ambient temperatures (i.e. in cold, "northern" climates and mountain areas, in general) or extreme heights (i.e. in aviation and aerospace).

**DIN 51825 KPHC1G-50; ISO 6743/9 L-X-EBHB1**

CODE	GRADE/NLGI	PACKAGING
JG10031	1	DRUM 180KG
JG10036	1	15KG (PAIL)
JG10042	1	12 X 0,4KG



## INNOVA™ CYBIO

Premium, readily biodegradable, EP-enhanced, multipurpose, synthetic grease with excellent anti-corrosion/-rust properties, ideal for exposed, environmentally sensitive marine/industrial applications and, even, off-road farming and earthmoving equipment. It will, equally, provide for superior, stress-free lubrication of roller/slide bearings, conveyor and drive chains, steel ropes, cables, stabilizers, water turbine guide vane bearings and screw pumps in either sea-going vessels or rigs and wastewater/water treatment plants, for example.

**DIN 51825 KPE2K-30; ISO 6743/9 L-X-CCIB2; OECD 301-B**  
**Biodegradability >60%; EPA 2013 VGP-compliant**

CODE	GRADE/NLGI	PACKAGING
JG14531	2	DRUM 180KG
JG14536	2	15KG (PAIL)



## INNOVA™ SYNCOMPLEX/FG-HT

Very high performance, aluminum complex-thickened, synthetic grease enforced with PTFE (Teflon®), ideal for high temperature (well above 180°C) applications in the foodgrade industry, such as in conveyor belts and chains, bakery/brick oven equipment, wafer baking equipment, film stretching tenders or plant high-temp fans and vacuum pumps or, even, the glass industry, kiln truck wheels, load rollers in copying machines and textile dryers.

**DIN 51825 KPHCF2P-50; ISO 6743/9 L-X-EEHB2; NSF H1**

CODE	GRADE/NLGI	PACKAGING
JG11036	2	15KG (PAIL)
JG11042	2	12 X 0,4KG



## INNOVA™ SYNCOMPLEX/FG-LT

Long service, EP-enhanced, anhydrous calcium-thickened, fully synthetic grease, specifically intended for the lubrication of bearings, sliding mechanisms and equipment operating in extremely low temperature environments in the foodgrade/food processing and beverage industries, such as industrial freezers and chillers, fans and refrigerating compressors/"cold room" control equipment, small electric motors and robots. It is equally ideal for use in the pharmaceutical and cosmetics/personal care industries.

**DIN 51825 KPHC1H-60; ISO 6743/9 L-X-ECHB1; NSF H1**

CODE	GRADE/NLGI	PACKAGING
JG11536	1	15KG (PAIL)
JG11542	1	12 X 0,4KG



## INNOVA™ COMPLEX/FG-GL

Performance, water-resistant, clean, non-toxic, calcium sulphionate complex-thickened, grease enforced with EP/AW additives, suitable for the general lubrication of bearings, bushings and linkages of all kinds of food processing equipment, e.g. bakery equipment, food processing equipment, multi-pack cassette bearings, wrapping machines, conveyor bearings, bottling machines support equipment, trolleys, etc.

**DIN 51825 KP2N-20; ISO 6743/9 L-X-BDHB2; NSF H1**

CODE	GRADE/NLGI	PACKAGING
JGI2036	2	15KG (PAIL)
JGI2042	2	12 X 0,4KG





## PREMUS™ MLB

Premium, high performance, lithium-soaped grease, enhanced with EP/AW additives and MoS2 for heavily-loaded, harsh (i.e. in the presence of water, dust, sludge or mud) applications requiring extremely high wear and friction control and water resistance. Highly recommended for suspension or steering joints, fifth wheels, slow-running bearings, open gears, etc. to be found in construction sites, earthworks or quarries.

**DIN 51825 KPF2K-25; ISO 6743/9 L-X-CCHB2**

CODE	GRADE/NLGI	PACKAGING
JG06531	2	DRUM 180KG
JG06536	2	15KG (PAIL)



## PREMUS™ GRF

Premium, heavy duty, lithium-soaped grease, enhanced with extreme pressure additives and graphite with excellent thermal/mechanical stability, providing for outstanding dry lubrication (i.e. when/if the lubricant base of the grease is removed) to all types of loaded/shocks-subjected bearings and mechanisms (e.g. pump vanes, steam traps) operating under high temperatures or/and low/high speeds.

**DIN 51825 KPF2K-25; ISO 6743/9 L-X-CCEB2**

CODE	GRADE/NLGI	PACKAGING
JG06031	2	DRUM 180KG
JG06036	2	15KG (PAIL)



## PREMUS™ LEP

Premium quality, multipurpose, smooth-textured lithium-soaped grease, enhanced with extreme pressure additives, with excellent anticorrosion properties and very high thermal/mechanical stability, suitable for all types of loads/shocks-subjected plain and roller bearings of a wide range of machinery/mechanisms to be found in automotive, off-road/farming, industrial, railroad and marine environments.

**NLGI 2: DIN 51825 KP2K-25; ISO 6743/9 L-X-CCHB2**  
**NLGI 3: DIN 51825 KP3K-25; ISO 6743/9 L-X-CCHB3**

CODE	GRADE/NLGI	PACKAGING
JG05031	2	DRUM 180KG
JG05036	2	15KG (PAIL)
JG05042	2	12 X 0,4KG
JG05531	3	DRUM 180KG
JG05536	3	15KG (PAIL)



## PREMUS™ AUTO

Premium quality, smooth-textured lithium-soaped semifluid grease, enhanced with extreme pressure additives with excellent anticorrosion properties and thermal/mechanical stability, ideal for use in central lubrication systems or for chassis lubrication of road/off-road vehicles and equipment operating in the farming, construction, industrial and, even, marine sectors.

**DIN 51826 GP00H-20; ISO 6743/9 L-X-BBEB00**

CODE	GRADE/NLGI	PACKAGING
JG13536	00	15KG(PAIL)
JG13538	00	4 X 4KG



## PREMUS™ LI

Premium quality, multipurpose, smooth-textured lithium grease with excellent anticorrosion properties and efficient thermal/mechanical stability, suitable for all types of plain and roller bearings of a wide range of machinery/mechanisms to be found in automotive, off-road/farming, industrial and marine environments.

**NLGI 2: DIN 51825 K2K-25; ISO 6743/9 L-X-CCHA2**  
**NLGI 3: DIN 51825 K3K-25; ISO 6743/9 L-X-CCHA3**

CODE	GRADE/NLGI	PACKAGING
JG04031	2	DRUM 180KG
JG04036	2	15KG (PAIL)
JG04038	2	4 X 4KG
JG04531	3	DRUM 180KG
JG04536	3	15KG (PAIL)
JG04538	3	4 X 4KG



CERTIFIED  
CYCLON QUALITY



## PREMUS™ COT

Special, green/blue-ish, lithium-thickened, semifluid grease intended for the lubrication of cotton pickers, enhanced with anti-rust and anti-corrosion additives. It is ideal for low temperature processes.

**DIN 51826 GP00H-20; ISO 6743/9 L-X-BBE00**

CODE	GRADE/NLGI	PACKAGING
------	------------	-----------

JG03531	00	DRUM 180KG
JG03536	00	15KG (PAIL)



## PREMUS™ LI-CA

Premium quality, versatile, multipurpose, mixed soap grease, insoluble in water with excellent mechanical and thermal stability, ideal for the lubrication of bearings and mechanisms in harsh automotive (heavy duty/off-road) and industrial environments where vapour, water, dust, mud and elevated temperatures are a common burden.

**NLGI 1: DIN 51825 K1K-20; ISO 6743/9 L-X-BCEA1**

**NLGI 2: DIN 51825 K2K-20; ISO 6743/9 L-X-BCEA2**

**NLGI 3: DIN 51825 K3K-20; ISO 6743/9 L-X-BCEA3**

CODE	GRADE/NLGI	PACKAGING
------	------------	-----------

JG01531	1	DRUM 180KG
JG01536	1	15KG (PAIL)
JG01538	1	4 X 4KG
JG02031	2	DRUM 180KG
JG02036	2	15KG (PAIL)
JG02038	2	4 X 4KG
JG02042	2	12 X 0,4KG
JG03031	3	DRUM 180KG
JG03036	3	15KG (PAIL)
JG03038	3	4 X 4KG



## PREMUS™ CY-WR/OG

Heavy duty, water-resistant, tacky grease with enhanced load-carrying capabilities for humid/damp/wet shore and offshore applications, e.g. in wire ropes, slides, cranes chassis, open gears, pressure blocks and screws, nuts, splines, water pumps etc.

**DIN 51502 OGF2E-20; ISO 6743/9 L-X-BBHA2**

CODE	GRADE/NLGI	PACKAGING
------	------------	-----------

JGI4031	2	DRUM 180KG
JGI4036	2	15KG (PAIL)



## PREMUS™ CA

Highly mechanically stable, adherent, water-resistant, anhydrous calcium-soaped grease of excellent anti-corrosion/-rust properties and enhanced dropping point/maximum operating temperatures, intended for general lubrication use in moderate to harsh (mud, dust, water, seawater) automotive, industrial and offshore environments.

**NLGI 2: DIN 51825 K2E-20; ISO 6743/9 L-X-BBBA2**

**NLGI 3: DIN 51825 K3E-20; ISO 6743/9 L-X-BBBA3**

CODE	GRADE/NLGI	PACKAGING
------	------------	-----------

JG00531	2	DRUM 180KG
JG00536	2	15KG (PAIL)
JG00538	2	4 X 4KG
JG01031	3	DRUM 180KG
JG01036	3	15KG (PAIL)
JG01038	3	4 X 4KG



## PREMUS™ BNT

Specialised grease formulated with high viscosity base fluids and inorganic clay (bentonite), suitable for applications submitted to frequent cycles of high and low temperatures as well as in constant high temperature conditions going beyond 150°C. It is, in particular, recommended for electrical motor bearings on very hot ventilation systems.

**DIN 51825 K2P-20; ISO 6743/9 L-X-BEAA2**

CODE	GRADE/NLGI	PACKAGING
------	------------	-----------

JG13031	2	DRUM 180KG
JG13036	2	15KG (PAIL)

**MARINE**

 **MARINE  
LUBRICANTS**

Marine lubricants fulfill practically any lubrication need of all vessels. Cyclon MCLs, SOs and TPEOs are certified with approvals by international marine engine manufacturers.

They can be delivered directly to any port of Greece. In addition, through international cooperations, CYCLON marine lubricants can be delivered in main ports abroad.

Cyclon marine lubes are continuously supported by our technical and laboratory experts and our suite of after-sales support services ID Lube Check®.

**Marine lubricants -manufactured in the EU- fulfill  
all lubrication needs of modern fleets**











## NAUTILUS LS

Cylinder oil (SAE 50, BN 40) of superior quality. Developed for two-stroke engines running in low sulphur heavy fuel oil (HFO). Specially formulated, it protects the piston ring and liner from wear without leaving any deposits. It is optimized for low sulphur (up to 1.5% weight) fuel.

MAN ES (NOL), WinGD (NOL)

CODE	GRADE/SAE	PACKAGING
JS00500	50	1000L
JS00501	50	208L



## NAUTILUS HEAVY XT

A novel technology, top quality cylinder oil of very high alkalinity reserves (TBN: 100) designed for the lubrication of marine cylinders of ultra low-speed, two-stroke marine diesel engines running on residual fuel. It ensures the effective neutralization of acids and protection of liner. It is suitable for the cylinder lubrication of very demanding crosshead marine diesel engines of new design (very long stroke) operating under "slow" steaming and burning residual fuel of high sulphur content (up to 3.0%).

MAN ES (NOL), WinGD (NOL), Mitsubishi

CODE	GRADE/SAE	PACKAGING
JS01000	50	1000L
JS01001	50	208L



## NAUTILUS HEAVY

A superior quality cylinder oil of high alkalinity reserves (TBN: 70), designed for low speed crosshead diesel engines that run on residual fuel. Due to its high detergent/dispersant properties, it ensures the effective neutralization of acids and protection of liner. It exceeds the requirements of MDT, WÄRTSILÄ (SULTZER) for two-stroke low speed diesel engines running under conditions of high stress. Suitable for use with engines burning residual fuel with sulphur levels no greater than 2.0%.

MAN ES (NOL), WinGD (NOL), Mitsubishi

CODE	GRADE/SAE	PACKAGING
JS01500	50	1000L
JS01501	50	208L



## NAUTILUS VLS/25

Premium quality cylinder oil designed for two-stroke marine engines running on ultra low sulphur distillate fuels or/and natural gas (LNG), methanol, ethane and LPG. It has been developed for heavy-duty marine diesel engines operating in emission control areas (ECA) running on fuel with a very low sulphur content (up to 0.1% after January 1st 2015 in ECAs). It is highly recommended for two-stroke marine applications that demand the use of up to 0,5% sulphur fuel (outside ECAs).

MAN ES, WinGD

CODE	GRADE/SAE	PACKAGING
JS02501	50	208L



CERTIFIED  
CYCLON QUALITY



## ARMOR MEDIUM

System oil for marine crosshead diesel engines with sufficient alkalinity to neutralise any strong acids, which may enter the crankcase from the combustion of fuel. It has enhanced load-carrying ability in order to reduce wear in heavily- loaded bearings. Recommended for use as a system oil in high-output, crosshead diesel engines, as well as a piston cooling medium. It can be used in small trunk piston engines whose fuel contains less than 0.5% in sulphur.

**MAN ES (NOL), WinGD (NOL), Mitsubishi, Kemel**  
**Meets: API CC**

CODE	GRADE/SAE	PACKAGING
JS03000	30	1000L
JS03001	30	208L



## POSEIDON DT

High performance diesel engine oils developed for use in trunk piston engines operating on low sulphur distillate fuels in marine and industrial applications. The DT series is intended for use as cylinder and bearing lubricants in many types of medium- and high-speed engines operating on distillate fuels or light fuel blends.

**MAN ES, Wärtsilä**  
**Meets: API CF**

CODE	GRADE/SAE	PACKAGING
JS06500	30	1000L
JS06501	30	208L
JS07000	40	1000L
JS07001	40	208L



## POSEIDON SX

Premium quality marine diesel engine oils, designed for use in medium-speed trunk piston engines. They provide superior wear performance, cleanliness and stability on powertrains that operate on distillate fuels. They maintain engine efficiency. Suitable for highly-rated, medium-speed diesel engines operating under high load conditions and operating on distillate fuels of up to 2% sulphur content. They may, also, be used in other marine applications, including gears reduction systems, where specialist lubricants are not required.

**MAN ES, Wärtsilä**  
**Meets: API CF**

CODE	GRADE/SAE	PACKAGING
JS07500	30	1000L
JS07501	30	208L
JS08001	40	208L



## POSEIDON TN

Premium quality marine diesel engine oils, designed for use in medium-speed trunk piston engines. They provide superior wear performance, cleanliness and stability on powertrains that operate on distillate fuels. They maintain engine efficiency. Suitable for highly-rated, medium-speed diesel engines operating under high load conditions and operating on distillate fuels of up to 2% sulphur content. They may, also, be used in other marine applications, including gears reduction systems, where specialist lubricants are not required.

**MAN ES, Wärtsilä**  
**Meets: API CF**

CODE	GRADE/SAE	PACKAGING
JS08500	30	1000L
JS08501	30	208L
JS09001	40	208L





## POSEIDON HT/20

Premium trunk piston engine oils specifically designed for use in medium-speed engines operating on 0.50% and 0.10% sulphur fuels and LNG. Boosted with advanced, versatile chemistry to be able to cover for engines operating on IMO-compliant residual, blended and distilled fuels but also for alternating natural gas dual-fuel engines. They are intended for main propulsion sources, for auxiliary use, or for certain generators (running mainly at part load) in offshore and shore environments. They can be used with fuels containing up to 2% sulphur. Also suitable for reduction gears and certain ship-board applications, according to OEMs' guidelines.

**MAN ES (NOL), Wärtsilä, Rolls-Royce, Yanmar, Daihatsu, MaK, Hyundai HiMSEN**  
**Meets: API CF**

PRODUCT	CODE	GRADE/SAE	PACKAGING
HT/4020	JS30500	40	1000L
HT/4020	JS30501	40	208L
HT/3020	JS31000	30	1000L
HT/3020	JS31001	30	208L



## POSEIDON HT

Specially designed crankcase lubricants for highly-rated, medium-speed, diesel engines operating on heavier fuels. Their high detergent potential provides excellent engine cleanliness, hence protecting vital parts of the engine from wear. Their use allows easy separation of contaminants in centrifugal separators. HT series are suitable for use in medium-speed diesel engines, in marine propulsion and power generation applications using fuel of higher sulphur contents. They are suitable for use in the most demanding highly-rated, turbocharged, medium-speed, diesel engines.

**MAN ES (NOL), Wärtsilä (NOL), Rolls-Royce, Yanmar, Daihatsu, MaK, Hyundai HiMSEN**  
**Meets: API CF**

PRODUCT	CODE	GRADE/SAE	PACKAGING
HT/3030	JS03500	30	1000L
HT/3030	JS03501	30	208L
HT/4030	JS04001	40	208L
HT/4040	JS04501	40	208L
HT/4050	JS05001	40	208L



## CYBIO-STETUB


Environmentally acceptable lubricant formulated with carefully selected ester base-stocks and high performance additive chemistry. It ensures the optimum lubrication (in both neat and emulsion forms) of stemtube and stabilizer applications in sensitive environments where fluid loss or water ingress may occur. Being inherently highly biodegradable, it is defined as "environmentally sensible fluid" as US EPA 2013 VGP specifies, meeting the strict requirements of all major stern seal manufacturers.

**US EPA VGP (2013)**  
**Meets: EU Ecolabel criteria**

CODE	GRADE/ISO	PACKAGING
JS05501	100	208L
JS06001	150	208L



CERTIFIED  
CYCLON QUALITY



**MARINE**





LPC S.A is an industrial and commercial corporation, member of Motor Oil Hellas Group of companies, and a pioneer in the lubricants sector, being active in the production of base oils and the manufacture and marketing of packaged lubricants.

The main products of the company LPC base oils and CYCLON lubricants have international presence in more than 30 countries.

LPC S.A is widely known, both for the high quality of the production technologies and process innovations it employs, as well as for its commercial and professional consistency.



An impressive number of international and Greek companies trust our company for the production of their products.

The sole target of LPC is to ensure the overall satisfaction of its customers, utilizing a rapidly growing sales network and by offering top quality products and excellent services around the world.











**LPC S.A.**  
124 MEGARIDOS AVE. | 193 00 ASPROPYRGOS | GREECE  
**T:** +30 210 8093900 | **F:** +30 210 8093999  
[www.cyclon-lpc.com](http://www.cyclon-lpc.com)